

REMINGTON ARMS COMPANY, INC.

SUCCESSOR TO THE REMINGTON ARMS UNION METALLIC CARTRIDGES CO., INCORPORATED.

MANUFACTURERS OF

FIREARMS, AMMUNITION, CUTLERY, CASH REGISTERS, ETC.

LONOKE, ARKANSAS

APRIL 30, 1992



TO: T. C. DOUGLAS
FROM: E. I. HERRING, III *E. I. H.*
SUBJECT: MONTHLY REPORT - APRIL, 1992

- o The SAAMI Pistol & Revolver Round Robin test for April has been completed, and the test results forwarded to the SAAMI office.
- o SAAMI Reference Ammunition - A new lot of 22-250 Rem SAAMI Reference Ammo has been qualified and announced to the industry.
- o At the request of Tim McCormack in the Ilion Custom Shop, a proof-load cartridge for the 22 Hornet was developed. A small quantity was handloaded and sent to the Custom Shop to cover their immediate requirements.
- o Olin Powder has submitted three powder samples for our evaluation:
 - WPR-289 - is WC-293 with flash suppressant added for 9mm Luger
 - WPR-287 - is 1000-2000 psi faster than WPR-289, also for 9mm Luger
 - WPR-780 - an improved lot for re-evaluation in the 270 Win 130 PSP cartridge
- o Norinco (North China Industries Company) submitted a sample of NM-04 shotshell powder for evaluation in the GL12-8 promotional load. This powder gave very good ballistic performance at room temperature (+70 F) and at +150 F, but gave low velocity and pressures at -20 F. Test results have been sent to Mr. Li Wanghan at Beta Chemicals for review. This powder was designed to be equivalent to Hercules Red Dot.
- o A new SAAMI Velocity Data Interpretation has been drafted and submitted to the members of the Pressure Measurement Sub-committee for approval. Drafts for CF rifle, CF pistol and revolver, Rimfire, and Shotshell were submitted for their review.
- o 220 Swift 60 HP Proof - A proof load was developed using the Sierra 60 HP bullet and Remington shells. An instruction letter has been issued listing the loading data for the 220 Swift Proof load.
- o A proof load has been developed for the 40 S&W cartridge. This proof load uses the 180 JHP bullet, 6.40 grains of Hercules Bullseye powder, and generates a pressure of 48600 psi. The proof pressure for the 40 S&W is 47000 psi to 50500 psi. All testing has been made using brass shells. Final testing will be performed in nickel plated shells when these become available.

T. C. Douglas
April Monthly Report
Page 2

o Biodegradable Wad Status:

Bio Wads - No evidence of degradation after nine months exposure.
Mortile TVL-50 - Samples continue to develop stress cracks and fracture easily. Control sample indoors - no change.

o Instruction letters have been issued for the RTL20M-9 20 ga. 1 oz. skeet load, and the 220 Swift 50 PSP cartridge.

o Gordon Taylor from ICI/Nobel Explosives Company in Scotland visited the plant on 4/29/92. NEC will continue to work on developing a magnum rifle powder for us to replace the IMR 7828 and 7816 powders. In addition, an order was placed for 22,000 pounds of NEC Rifle 0 powder, which is a replacement for IMR 4350. NEC will also submit samples of Neodisc 3 and Neodisc 3F for evaluation in the GL12 promotional shotshell.

o On 4/29/92, Duane Kruse at Olin's Powder Operations in St. Marks, Florida, notified us that a transaction had been approved by Olin's Defense Systems Group to sell their Olin Ordnance Division to Alliant Techsystems Inc. The sale will include the Olin Powder Operations. Alliant Techsystems is a subsidiary of Honeywell, Inc., and is a major supplier of large caliber ammunition. Duane does not anticipate any changes in operation.

o A sample of 30 Carbine 168 BTHP cartridges was loaded and sent to Knight's Armament Company for evaluation in a SWS suppressed sniper rifle. Although these cartridges are not subsonic (loaded to 1308 fps), they do provide a low sound signature and should be effective.