

NEAR FIRE CONTROL DESIGN OBJECTIVES

- NON INTERCHANGABLE WITH M/700
- USER "FRIENDLY" DESIGN
- IMPROVED "TACTILE FEEL" OF THE TRIGGER
- IMPROVED "TACTILE FEEL" OF THE SAFETY (TWO POSITION)
- CUSTOMER ABLE TO OPEN AND CLOSE BOLT WITH SAFETY "ON"
- BOLT LOCKED DOWN IN A "S" CONDITION
- CUSTOMER ADJUSTABLE TRIGGER PULL FORCE ONLY WITHIN PRESCRIBED LIMITS
- BOLT STOP RELEASE RELOCATED WITH IMPROVE "TACTILE FEEL"
- LEFT HANDED VERSION TO BE DESIGNED
- DESIGN FOR MANUFACTURABILITY PRINCIPLES UTILIZED
- DESIGN FOR ASSEMBLY PRINCIPLES UTILIZED
- "SEALED" DESIGN ROBUST AGAINST TAMPERING
- RIFLE WILL NOT FIRE IF TRIGGER PULLED AND HELD AS SAFETY IS MOVED FROM "S" TO "F"
- ROBUST AGAINST IMPACT
- COMPEL TRIGGER TO SUPPORT POSITION IN MOVING SAFETY FROM "F" TO "S"
- "NO LUBRICATION" DESIGN
- ENHANCED CORROSION RESISTANCE

D.S Findlay  
11-5-93

NBAR - DSF



