

R2522681
BARBER - PRESALE R 0121693

1954	2
1955	3
1956	4
1957	5
1958	6
1959	7
1960	8
1961	9
1962	10
1963	11
1964	12
1965	13
1966	14
1967	15
1968	16
1969	17
1970	18
1971	19
1972	20
1973	21
1974	22
1975	23
1976	24
1977	25
1978	26
1979	27
1980	28
1981	29
1982	30
1983	31
1984	32
1985	33
1986	34
1987	35
1988	36
1989	37
1990	38
1991	39
1992	40
1993	41
1994	42
1995	43
1996	44
1997	45
1998	46
1999	47
2000	48
2001	49
2002	50
2003	51
2004	52
2005	53
2006	54
2007	55
2008	56
2009	57
2010	58
2011	59
2012	60
2013	61
2014	62
2015	63
2016	64
2017	65
2018	66
2019	67
2020	68
2021	69
2022	70
2023	71
2024	72
2025	73
2026	74
2027	75
2028	76
2029	77
2030	78
2031	79
2032	80
2033	81
2034	82
2035	83
2036	84
2037	85
2038	86
2039	87
2040	88
2041	89
2042	90
2043	91
2044	92
2045	93
2046	94
2047	95
2048	96
2049	97
2050	98
2051	99
2052	100
2053	101
2054	102
2055	103
2056	104
2057	105
2058	106
2059	107
2060	108
2061	109
2062	110
2063	111
2064	112
2065	113
2066	114
2067	115
2068	116
2069	117
2070	118
2071	119
2072	120
2073	121
2074	122
2075	123
2076	124
2077	125
2078	126
2079	127
2080	128
2081	129
2082	130
2083	131
2084	132
2085	133
2086	134
2087	135
2088	136
2089	137
2090	138
2091	139
2092	140
2093	141
2094	142
2095	143
2096	144
2097	145
2098	146
2099	147
2100	148
2101	149
2102	150
2103	151
2104	152
2105	153
2106	154
2107	155
2108	156
2109	157
2110	158
2111	159
2112	160
2113	161
2114	162
2115</	

62391-8

THIS DRAWING OR INFORMATION IS
PROPRIETARY INFORMATION TO THE
REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING: WORK TO FIGURES
UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE (.1) — TOLERANCE ± .015
2 PLACE (.01) — TOLERANCE ± .010
3 PLACE (.001) — TOLERANCE ± .005
8 ON FRACTIONAL DIMENSIONS ± 1/64
8 ON ANGULAR DIMENSIONS ± 0°-30'
FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS
ACCEPTABLE, UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE .250 OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL 1035 OR 1036
HEAT TREAT _____
HARDNESS _____
COLOR _____
HEAT TREAT AND COLOR TO BE DONE BY
REMINGTON P&J 6-6-80

ALTERATIONS

ALT.	WAR	REF.	BY	DATE
1		ADD MODEL 7LWT.	JW	4/12/84

NOTE:
MAX. ECCENTRICITY OF POINT AND SHANK .003 (.006 T.I.R.)
MAX. ECCENTRICITY OF .410-.405 DIA AND SHANK .003 (.006 T.I.R.)

FOR FINISH DRAWING
SEE B-15410

THIS DRAWING OR INFORMATION IS
PROPRIETARY INFORMATION TO THE
REMINGTON ARMS COMPANY, INC.

7LWT.		FIRING PIN BLANK	
XP-100		" "	
MOHAWK	600	FIRING PIN	
MODEL	PART NO.	PART USE	
DES. BY DATE	DRN. BY DATE	CHK. BY DATE	APP. BY DATE
	5-16-80	5-21-80	JW 5/21/80
TITLE FIRING PIN BLANK			
NUMBER	SCALE	SUPERSIDES	PERMITS
B-16509	4X		
REMINGTON ARMS CO. 100 HIGH RESEARCH DIV.			