## CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
ELIZABETHTOWN, KY 42701...

## Clean & Inspect Checklist

Model: 710 Short	Action Caliber 243 & 308
Project: 241429	TLW #: TEW1876
Date:/	
Gun Test #	S/N
Round Level:	Inspector:
Measure Headspace	
Check Takedown Screw Torque @ Disassembly: Frt	, Center, Rear
l Scar Engagement: 1 <sup>st</sup> 2 <sup>nd</sup> 3 <sup>cd</sup>	Ave spec020" to.025"
Reset Sear Engagement if Required: 18 2 <sup>nd</sup> .	3 <sup>rd</sup> Ave
] Trigger Pull; 1 <sup>st</sup> 2 <sup>nd</sup> 3 <sup>rd</sup>	Ave spec- 4 lb. to 5.5 lb.
Reset Trigger Pull if Required: 1 <sup>st</sup> . 2 <sup>nd</sup> .	3 <sup>rd</sup> Ave
Inspect Magazine components for wear or damage	
Other items of	
note:	
l Torque Takedown Screws & Reassembly: SPEC- Frt-	50 in the Center- 30-35 in the Rear- 15 in the
	to many content to be many real to many
	TLW18

Subject to Protective Order - Williams v. Remington