

1999	5871	17 Remington
2000	6344	223 Remington
2001	6342	7mm-08 Remington
2002	6348	221 Remington Fireball
2003	5869	300 Savage

Model 700 ADL can be converted to the BDL with hinged floorplate style but not to a detachable magazine. Dimensions of the detachable magazine receivers are different and key parts are not interchangeable. Please contact your local Remington authorized repair center or parts distributor for pricing information. To perform the conversion to a hinged floorplate you will need the following parts:

BDL style stock  
Trigger guard  
Trigger guard Screws  
Magazine box  
Magazine spring  
Mag. Follower

Remington Arms Co., sells only complete firearms. We do not offer actions-only, or barreled actions at the current time.

**NEVER** remove the trigger mechanism, or make adjustments to the trigger or trigger assembly. This can put your firearm in an unsafe condition. All adjustments to the trigger must be made by the FACTORY OR A REMINGTON AUTHORIZED REPAIR CENTER.

Remington makes synthetic stocks that will fit most right hand Model 700 rifles. It is a simple change that can be made with no special skills required with common household tools.

When ordering a replacement stock, it will need to be for the same type (ADL, BDL, BDL-DM, Mtn, Varmint, Sendero) and same action (short action, long action, long action magnum).

Standard production Model 700 rifles utilize a hammer forged rifled barrel. A mandrel for rifling is inserted in the barrel bore and imprints the rifling. Custom Shop Rifles are button rifled.

The differences between the Model 700 Sendero and the Model 700 Varmint is that the Sendero is available in long action calibers and the Varmint is available in short action calibers. Both have a synthetic stock which houses a full-length aluminum bedding block that leaves the barrel completely free-floating. This is a huge selling feature. This is only available in some synthetic stocks. You cannot have an aluminum bedding block in a wood stock. The purpose of the aluminum bedding block is to stabilize the barrel. For the wood stocks, people can bed their stocks using fiberglass, epoxy, or other material. (This will void their warrant on the stock) The Sendero and the VSSF have fluting on the barrel. This cools the barrel faster and makes for better heat dispersion making the barrel more rigid than a barrel of the same weight that has not flutes.

The front and rear sights can be removed from the Model 700. They are attached to the barrel by two screws each. Once removed, the holes from these can be plugged with the receiver plug screws located on the top of the receiver.

Recoil pads for the Model 700 are not fitted they are flat. Butt plates for the Model 700 are fitted. Recoil pads must be cut to fit the stock (wooden stocks). We do not recommend that consumers