

inches) provided by an adjustable aluminum butt plate assembly. High comb on stock to facilitate the use of telescopic sights. Palm-swell on both sides of grip. The rifle Beavertail-type fore-end. An aluminum channel extends full length of fore-end. The sling swivels, magazine floor plate and trigger guard are attached to the channel for additional strength. Equipped with a Harris (short) bipod.

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#EFEFE7" height="24">

Weight:</td>

<td width="79%" valign="top" bgcolor="#EFEFE7" height="24">

Rifle, bipod and scope weigh 13lbs/13oz. The complete system, including carrying case weighs 55 pounds.</td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#FFFFFF" height="80">

Accessories:</td>

<td width="79%" valign="top" bgcolor="#FFFFFF" height="80">

include a foam-lined, heavy-duty, fiberglass carrying case (manufactured by an outside contractor and costing \$505 apiece) and soft cases for the rifle and scope. Other accessories include iron sights, cleaning equipment, manuals, bipod, sling swivels, M1907 sling and a spare parts kit.</td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#EFEFE7" height="60">

Reconditioning contracts:</td>

<td width="79%" valign="top" bgcolor="#EFEFE7" height="60">

The initial contract was awarded to Remington to repair/recondition the U.S. Governments Sniper Weapons Systems between August 1992 and August 1997. The 2nd contract currently runs from August 1997 to August 2002. It was noted that over 10,000 rounds had been shot in some SWS barrels.</td>

</tr>

</table>

</td>

</tr>

</table>

<table border="0" cellspacing="0" width="100%" id="AutoNumber12" cellpadding="0">

<tr>

<td width="100%"> </td>

</tr>

<tr>

<td width="100%" bgcolor="#A2A7A3">

</td>