

NOTE: The top right edge of the slide may bind on the bottom front edge of the ejection port in the receiver. To free the slide, push the front end of the bolt down. See Picture 15.

9. Lift the breech bolt assembly and slide assembly from the rear of the action bars.

NOTE: Steps 10-12 are for the Model 070™ Super Magnum™ ONLY.

10. Turn breech bolt assembly upside down. (Refer to **NOTE** after step 8.)


11. Place a small thin-bladed screwdriver under tab of port cover and lift slightly. See Picture 16.

12. Slide port cover rearward from the breech bolt assembly.

13. Tap out the front and rear trigger plate pins. See Picture 15.

14. Lift the rear of the trigger plate assembly, slide rearward and remove from the receiver.

WARNING! DO NOT allow the firing pin to hang forward when the trigger pin is removed. This can best be assured by keeping the safety mechanism engaged at all times. **REM GUNS WILL NOT SHOOT.**



PICTURE 15



NOTE: PORT COVER USED ON MODEL 070™ SUPER MAGNUM™ ONLY.


PICTURE 16

Lubrication And Maintenance

WARNING! Look into the ejection port and do not look through the sights when the gun is cocked. Make it a habit to look into the ejection port before cocking or loading.

TO CLEAN THE BARREL:

1. Use the instructions and the equipment provided in a good shotgun cleaning kit. For recommendations, see your Remington® Authorized Gunsmith or dealer.
2. Select the correct gauge cleaning brush and attach the brush to the cleaning rod.
3. Put the cleaning brush into gun cleaning solvent.
4. Push the cleaning rod through the barrel several times.
5. Push the correct size cleaning patch through the barrel.
6. Repeat several times using a clean patch each time until the patch is not dirty.
7. Remove all smoking residue from the locking collar. See Picture 17.



PICTURE 17

TO CLEAN THE CHOKE TUBE:

1. Remove the choke tube from the barrel.
2. Clean the choke tube including the threads with good cleaning solvent and wipe dry.
3. Apply Rem™ Oil on threads and reassemble the choke tube to the barrel following the instructions on page 10.

WARNING! After cleaning, make sure the choke tube is properly seated.

THE BREECH BOLT ASSEMBLY:

Clean as a unit. Brush with cleaning solvent and wipe clean and dry.

THE RECEIVER:

Brush the inside of the receiver with cleaning solvent and wipe dry.


WARNING! There may be sharp edges inside the receiver. Keep fingers covered or gloved when wiping.

THE TRIGGER PLATE ASSEMBLY:

NOTE: Clean as a unit with Rem™ Oil only. See **NOTE** at the bottom of page 14.

Spray the trigger plate assembly with Rem™ Oil as shown. See Picture 18. Let stand for 15 minutes. Spray again to wash out solvents. Shake off excess lubricant.

WARNING! Do not use grease or other non-solvent lubricant to oil a Remington® rifle. It will collect dirt and ruin the rifle.



PICTURE 18