BARBER - REM DOCSB0013705

Bolt: The bolt consists of: Bolt body Firing pin assembly Bolt handle Jeweling (available on some models lazer etched on) (design on the bolt) Last 4 numbers of the serial number (will match from the receiver), Bolt assemblies are restricted and are factory installed only! Safety: Our safety is a positive click safety. (We will not make it quieter!!) This is to ensure that you know that you have taken your firearm off of safety. Trigger Assembly: All of the parts in the trigger assembly are restricted. We do not recommend any adjustments to the trigger screws. This will void the warranty on the trigger and can put the firearm in an unsafe condition. Factory specifications at the current time are no less than 4 ½ pounds (we will not go lighter due to liability issues) Trigger Guard Screws: The ADL version has front rear; and center guard screws. All other Model 700's have only front and rear trigger guard screws. Trigger guard screws on synthetic and wood are tightened to a hand tight fit. VS and Sendero trigger guard screws are tightened to no more than 45 inch pounds. Police trigger guard screws are to be tightened to no micre than 45 inch pounds. Too much will crack the stock. Reinforcement Screws: This screw helps with the strength of the stock, it keeps it from splitting. Long action and long action mags have 2 short action has 1 twill look like a black dot on the stock. Recoil Lug: The recoil lug helps to direct the recoil into the stock, which lessens the amount of felt recoil. The lug is located in the barreled action. Stocks: Stocks come with a butt plate or recoil pad on magnums and grip cap. Grip cap and fore end tip are epoxyed on. Our free floated stocks do not have pressure points, 700 Mountain stocks will interchange with the Titanium rifle. Stocks that have cheek pieces: ADL (wood and synthetic) BDL (wood and synthetic) Mountain