

gunsamerica.com
auctionarms.com
gunfinder.net

To remove the bolt on the Model 600:

Thank you for contacting Remington Country. To remove the bolt, push safety forward to unlock the bolt and raise bolt handle. Pull the bolt rearward. Press down on the front of the bolt stop. The bolt stop is located in the left rear of the bolt channel in the receiver. Use a small flat key or screw driver. Allow the bolt to slide back and disassemble as bolt stop is passed. Lift bolt from the rifle.

If you will complete the form located through the link below we will forward to you a copy of the original owner's manual.

<http://www.remington.com/whatsnew/readroom.htm>

You can also find owner's manuals for some of our current models on-line in our Reading Room in the "What's New" Section.

700 Police vs 700 VS

Thank you for your interest in Remington products. Both have a stock produced by HS Precision. The 700 Police has a tactical stock with bipod swivel, wider fore-end, and larger palm swell on most. It offers a parkerized finish on the metal. Police models go through a 21 point inspection for quality and performance and have a guaranteed Minute of Angle.

- **597 Bolt does contain a "hole in bottom"**. Model is designed this way, has no function or safety issues with this. This is a result of the extractor pocket cutter breaking through the bottom side of the bolt.

ADL vs BDL

Thank you for contacting Remington Country. The ADL will have a blind magazine which means you can unload from the top only. The BDL will have a hinged floorplate of detachable magazine to unload from the bottom.

Adjusting the rifle sights

Thank you for contacting Remington Country. Move the rear sight in the same direction as you need to move the bullet on the target. There is a windage and elevation screw that should be loosened to make the following adjustments.

If the bullet hits above the center, slide the rear sight down (backward) on the ramp.

If the bullet hits below the center, slide the rear sight up (forward) on the ramp.

If the bullet hits to the left, slide the rear sight aperture to the right.

If the bullet hits to the right, slide the rear sight aperture to the left.

Lines on the rear sight

Thank you for contacting Remington Country. The lines do not represent a specific distance. They are merely a guide for you in learning your particular rifle. You can use them as a individual guide for the distance you are trying to achieve after sighting in your particular barrel.

Nylon 66 stock replacement