

Product Specs

Model: 40-XS Hand: RT

Caliber: .308 Win

Stock Material ☐ WOOD ☒ SYNTHETIC ☐ LAMINATE Type/Color: Black H.S. PST25

Stock Finish ☐ HIGH GLOSS ☒ MATTE ☐ CAMO ☐ OTHER

Stock Notes Stock has adj. LOP & Comb. Add index marks to stock for ref. points.
See Ron Engell for method used on prototypes

Receiver Material ☒ STAINLESS ☐ CARBON ☐ STANDARD

Receiver Finish ☐ GLOSS ☐ SATIN ☐ BLAST ☐ BLACK OX ☒ POWDER COAT ☐ CAMO
(As submitted but will suggest to FBI that we switch to another method that allows for more consistent thickness control such as 2-part epoxy or Boron Carbide Ceramic Film in order to allow for bedding prior to color)

Receiver Bedding Action & Trigger Guard to be bedded w/ Iron Brigade Armory Method
Iron Brigade will train Remington to use this method.

Barrel Material ☒ STAINLESS ☐ CARBON ☐ STANDARD

Barrel Finish ☐ GLOSS ☐ SATIN ☐ BLAST ☐ BLACK OX ☒ POWDER COAT ☐ CAMO
(See Receiver Finish Notes above - same applies to barrel)

Barrel Profile STD 40-X

Barrel Bracket STD Stainless
(As submitted but will suggest FBI switch to Oversized lug from Badger Ordnance (Par

Barrel Length 24"

Twist Rate 1:10" (As submitted but will suggest FBI switch to 1:12" if contract is awarded)

Crown 40-X

Fire Control M700 Stainless Note: Trigger & safety arm must be powder coated or equivalent to ma

Trigger Pull Weight 3.75lbs

Headspace Must not exceed min + 0.002"

Bolt Finish ☐ CHROMED ☐ JEWELLED ☐ BLUED ☒ OTHER Powder Coat or Equivalent (See Receiver

Bolt Handle Bolt Handle to be roll pinned to bolt body in addition to brazing

Checkering N/A

Recoil Pad/Butt Plt STD H.S. Precision 1" Pad
(As submitted but will suggest FBI switch to R3)

Drop at Comb Adjustable

Drop at Heel Adjustable

Length of Pull Adjustable

Swivel Studs STD 700 Police/M-24 - Must be epoxied in place. MUST NOT BE REMOVABLE

Swivels Michaels of Oregon QD style swivels

Sling Turner AWS (Part #NMSRAWS Black)

Sights None, Clean Barrel (DRILL AND TAP FOR 8-40 THREADS)

Bases Badger Ordnance Steel Picatinny Style

Rings Badger Ordnance Steel

Scope Leupold VXIII 3.5-10x40 LR M1 (30mm tube) (shipped w/ Butler Creek Flip Open caps)

BiPod Harris LM-S Add Pod-Loc's

Special Ser # FBXXXX

Special Markings Twist rate must be rolled on barrel

Laser Engraving N/A

Special Packaging Pack in Pelican F97092 (Cut Foam to Fit rifle & Deployment Case)
All literature for component products to be packed with system.

Users Manual Model 40-XS User's Manual (derived from M-24, Trull has copy)

Accuracy Specs. 1/2" @ 100 yds. Testing will require shooting (5) 5-shot groups @ 100 yds w/
ammo listed below. Largest group will be dropped from results.
Remaining (4) groups to be averaged. Average should not exceed 1/2".