

**FBI Sniper Rifle Proposal
"Model 40-X S.W.A.T. Deployment Rifle"**

Three Complete Samples to FBI by 7/21/03

Product Specifications

- Model 40-X stainless steel right hand short action with M-24 Powder Coat Finish **Engell**
 - Serial Number to contain "FBI" suffix
 - Receiver rolled as Remington Model 40-X
 - Bolt will have same finish as M-24 bolt
 - Bolt handle will be welded to bolt body
 - Bolt plug will be powder coated to match receiver
 - Scope mounting holes will be over sized to 8-40 same as M-24
- Stainless steel 24" Model 40-X button rifled barrel with M-24 Powder Coat Finish **Engell**
 - Chambered for .308 Win (match chamber)
 - Twist rate 1:10 or 1:12 pending Engell's gallery test with Federal GM308M ammunition
 - Twist rate and caliber rolled on barrel
 - Standard 40-X barrel contour-no fluting
 - Protective crown
 - Must free-float in stock
 - Headspace must fall within 1.630" min and 1.634" max
 - Accuracy specification stated as ½ MOA 5-shot group out of box, 1 MOA after 5k rounds
- Model 700 stainless steel fire control **Engell/Leskovar**
 - Trigger pull set at 3.75 lbs
- Trigger floorplate assembly will be Sunny Hill all steel model **Engell**
- H.S. Precision Pro-Series 2000 Tactical Stock **Engell/Trull**
 - Adjustable comb
 - Add witness mark to comb and witness marks on stock for adjustment reference points
 - Adjustable length of pull
 - Add witness marks on either top or bottom butt pad posts to serve as adjustment reference points
 - Limbsaver/R3 recoil pad will be added in place of standard butt plate
 - Stock and magazine configuration must be configured to hold 5-rounds in the magazine (6-round total capacity for firearm)
 - Must be equipped with standard LE three swivel stud configuration
 - Color will be standard M-24 black
- Leupold Vari-X III 3.5-10x40 Long Range M1 scope with Mil-Dot reticle and 30mm tube (item #52128 Remington cost \$601.60 ea)