

CAL: 300 WIN MAG

PROJECT # 241314

CAL. 300 WIN MAG				ROUNDS AT START-0
NAME	DATE	TEST ACTIVITY	COMMENTS	RDS. FIRED
SW/PA	12/19/03	Out of box Inspection	FLW1303A	
JS	12/22/03	De-Torque Scope base bolt screws	Front 35 Rear 35	
BL	1	Headspace	min + .003	1
BL	1	Proof	OK	1
BL	12/22/03	Headspace	min + .003	
JS/BL	12/22/03	Depth Front Take down screw hole		
BL	12/23/03	Firing Pin Indent.	.014-.020-.020 Avg. .0196	
JS	12-29-03	Gear/Trigger Engagement	Ang. .031	
JS	12-29-03	Gear lift	.0158	
SW/JS	1/13/04	Change out bolt head		
SW/JS	1/13/04	Headspace	Min + .005	1
SW/JS	1/13/04	Proof Rd		2
SW/JS	1/13/04	Headspace after proof	Min + .005	200
SW	1/15/04	200 Rd Basic Jack Function Test		202
SW	1-15-04	Headspace - Min + .005	(Front/Center Takedown screw loose)	
BL	1-16-04	Shoulder Fire	Bolt stop not functioning properly / 1 FT Feed	20
			1 FTE	222
JS/BL	1-20-04	Clean & Inspect	See Inspection sheet	

Logform

Q

ET20160

Confidential - Subject to Protective Order

Williams v. Remington

CONFIDENTIAL

Remington Arms Company, Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Trial & Pilot Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-28

TLW #: TLW1303

Date: 01 / 20 / 04

Inspector: JS/BL

Round Level: 222

☒ Measure Headspace mint .005

☒ Sear Engagement: 1st. 030 2nd. 030 2^{3rd}. 0302

Ave. 0301 spec. .020" to .025"

Reset Eng
0258

☒ Trigger Pull: 1st. 4.594 2nd. 5.341 3rd. 5.469

Ave. 5.136 spec- 4 lb. to 5.5 lb.

☒ Check Take-Down Screws and Re-tighten if necessary.

☒ Inspect extractor & bolt face area. Some wear on bolt face

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive

wear: Locking lugs some wear, bolt stop worn

☒ Inspect stock for any signs of cracking or other failure.

☒ Other items of

note: magazine box protruding

TLW1303

Remington Confidential

ET20161