

CONFIDENTIAL

Remington Arms Company Inc.RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Firing Pin Indent – Series C After Live Fire Test.	10	0.01707 in.	0.00072 in.	0.01655, 0.01758
---	----	-------------	-------------	------------------

3.1.1.7 TLW04071 - Trigger/Sear Engagement

(T&P, Series "C") Specification: 0.020 to 0.025 inches.

Variable	N	Mean	Std. Dev.	95% Confidence Interval
Trigger/Sear Engagement	30	0.0278 in.	0.00209 in.	0.02705, 0.02854

Sear Lift, (T&P, Series "C"): specification: 0.006 to 0.018 inches.

Variable	N	Mean	Std. Dev.	95% Confidence Interval
Sear Lift	30	0.01578 in.	0.0017 in.	0.01531, 0.01624

3.1.1.8 TLW04074 - Measure Trigger Pull Forces

(T&P, Series "B" & "C"); specification: 4.0 to 5.5 lbs.

Variable	N	Mean	Std. Dev.	95% Confidence Interval
Trigger Pull Forces, in Stock Series B	30	3.99 lb.	0.375	3.85 lb., 4.13 lb.
Trigger Pull Forces, in Stock Series C				
Trigger Pull Forces, out of Stock Series B	30	4.17 lb.	0.334	4.05 lb., 4.30 lb.
Trigger Pull Forces, out of Stock Series C				

(Note: spring scale used for measurements.)

Aug. '01 - Trial & Pilot Test - Remington M710 Centerfire Rifle;
R & D Technical Center Project No. 241039; TLW 0407
file: F:\Test Reports\Firearms Tests\710 T&P_270\M710_270_T&P_REPORT_JUL01_Rev0.6.doc

Page 17

CONFIDENTIAL

REV.0.6 - 05/29/06 15:00 JCH

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R00032526

ETE00001625