

**CAL: 300 WIN MAG**

M/710 MAGNUM TRIAL AND PILOT TEST 1.1

TRACKING # TLW 1407  
PROJECT # 241314

| NAME     | DATE      | TEST ACTIVITY          | COMMENTS             | ROUNDS AT START-0 |            |
|----------|-----------|------------------------|----------------------|-------------------|------------|
|          |           |                        |                      | RDS. FIRED        | TOTAL RDS. |
| JW / BL  | 2/16/2004 | OUT OF BOX             | INSPECTION OK        |                   |            |
| SW / BL  | 2/16/2004 | HEADSPACE BEFORE       | PROOF MIN + .005     |                   |            |
| SW / BL  | 2/16/2004 | PROOF ROUND            |                      | 1                 | 1          |
| SW / BL  | 2/16/2004 | HEADSPACE AFTER        | PROOF MIN + .005     |                   |            |
| SW/JW/BL | 2/16/04   | INDENTS                |                      |                   |            |
| SW/BL    | 2/17/04   | SEAR LIFT              | SEE DATA SHEET       |                   |            |
| SW/BL    | 2/17/04   | ENGAGEMENT             |                      |                   |            |
| SW/BL    | 2/17/04   | TRIGGER PULL           |                      |                   |            |
| BL       | 2/19/04   | 200 Rd Jack funct.     |                      | 200               | 201        |
| JS       | 2/27/04   | 500 Rd Ext. Endur Test |                      | 500               | 701        |
| BL       | 3/9/04    | Clean/Inspection       | See Inspection sheet |                   |            |

Logform

3

ET21102

Confidential - Subject to Protective Order  
Williams v. Remington

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-18

TLW #: TLW1303

Date: 3 1 9 104

Inspector: BL

Round Level: 701

- ☒ Measure Headspace min .005
- ☒ Inspect Take Down Screws for loosening. center screw 1/8 turn 83
- ☒ Sear Engagement: 1<sup>st</sup>. .0354 2<sup>nd</sup>. .0358 3<sup>rd</sup>. .0356 Ave. .0356 spec- .025" to .030"
- ☒ Reset Sear Engagement if Required: 1<sup>st</sup>. .0289 2<sup>nd</sup>. .0281 3<sup>rd</sup>. .0277 Ave. .02823
- ☒ Trigger Pull: 1<sup>st</sup>. 5.069 2<sup>nd</sup>. 4.784 3<sup>rd</sup>. 4.831 Ave. 4.895 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>.      2<sup>nd</sup>.      3<sup>rd</sup>.      Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: cam surface, locking lugs some sign of wear
- ☐ Inspect stock for any signs of cracking or other failure.
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21103