

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JS	4/25/04	Head space	Mint. .001	TLW1447A	
"	"	Head space	Belt Type GO won't close	"	
SW/JS	4/25/04	Proof Rd	OK	TLW1447B	1
↓	4/26/04	Head space	Mint. .002	TLW1447C	
↓	"	Head space	Belt Type GO won't close	"	
SW	4/26/04	Firing Pin Indent	.018, .019, .018 Avg. .0183	TLW1447D	
↓	4/28/04	Check loosening	torque front screw 38 in lbs	TLW1447Z	
↓		Check depth of	front take down screw hole .0140		
↓		Check number of	turns to loosen front screw 2-turns		
↓		Inspect threads &	measure length OK/14465		
↓		Engagement	.0330, .0319, .0331, Avg. .03200	TLW1447E	
↓		Trigger Pull		TLW1447F	
↓		4.690, 4.700,	4.745, 4.730, 4.677, Avg. 4.706	"	
SW	4/28/04	Gear lift	.0194	TLW1447E	
SW	4/29/04	Torque front	screw 70 in lbs	TLW1447	
SW	5/3/04	200 Rd Basic	Jack Function Test	TLW1447P	200
BL	5-6-04	Clean Bore & Bolt			
SW	5/17/04	EX Function & Endurance Test	1 Multifunction	TLW1447R	500
SW	5/19/04	Clean & Inspect	Head space Mint. .002	TLW1447S	701

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS