

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-26

TLW #: TLW1447

Date: 5 / 19 / 04

Inspector: SW

Round Level: 701

☒ Measure Headspace Min +1.002

☒ Inspect Take Down Screws for loosening. Front Screw 1/4 Turn

☒ Sear Engagement: 1st. .0390 2nd. .0388 3rd. .0389 Ave. .0389 spec- .025" to .030"

☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Trigger Pull: 1st. 4.586 2nd. 4.639 3rd. 4.559 Ave. 4.595 spec- 4.5 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs little wear OK

☒ Inspect stock for any signs of cracking or other failure: OK

☐ Other items of note: _____

TLW1216

Remington Confidential

ET21763