

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JJ	4/25/04	Head space	Min +.001	TLW1447A	
"	"	Head space	Belt Type GO won't close	"	
SW/JJ	4/25/04	Prop & Rd	OK Hammer bolt back	TLW1447B	1
↓	4/26/04	Head space	Min +.001	TLW1447C	
↓	"	Head space	Belt Type GO won't close	"	
SW	4/26/04	Firing Pin Indent	.019, .018, .019 Avg. .0186	TLW1447D	
↓	7/28/04	Check Loosening torque front screw	4.5 in lbs	TLW1447Z	
↓		Check depth of front take down screw hole	.0140		
↓		Check number of turns to loosen front screw	2-turns		
↓		Inspect threads & measure length	OK / 1.4460		
↓		Engagement	.0346, .0342, .0343 Avg. .03436	TLW1447E	
↓		Trigger Pull		TLW1447F	
↓		4.359, 4.301, 4.368, 4.355, 4.355, Avg 4.348		"	
SW	4/28/04	Screw lift	.0159	TLW1447E	
SW	4/29/04	Torque Front screw	70 in lbs	TLW1447	
SW	5/4/04	200 Rd Brvic Jack Function Test		TLW1447P	200 201
EL	5-6-04	Clean Bare Bolt			
SW	5/17/04	EX-Function & Endurance Test	O-Mal Functions	TLW1447R	500 701
SW	5/19/04	Clean & Inspect	Head space Min +.002	TLW1447S	

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

CL