

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Extruded Receiver "Magnum Caliber"

Project: 241314

TLW #: TLW1689

Date: 2 / 22 / 05

Gun Test # A25

S/N 71203203

Round Level: 721

Inspector: B. LEE

83

- ☒ Measure Headspace min .005
- ☒ Check Takedown Screw Torque @ Disassembly: Frt 45, Center 30, Rear 10
- ☒ Sear Engagement: 1<sup>st</sup> .02972<sup>nd</sup>, .0312 3<sup>rd</sup> .0306 Ave. .0298 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup> \_\_\_\_\_ 2<sup>nd</sup> \_\_\_\_\_ 3<sup>rd</sup> \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Trigger Pull: 1<sup>st</sup> 4.786 2<sup>nd</sup> 4.676 3<sup>rd</sup> 4.750 Ave. 4.736 spec- 4.5 lb. to 6 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup> \_\_\_\_\_ 2<sup>nd</sup> \_\_\_\_\_ 3<sup>rd</sup> \_\_\_\_\_ Ave. \_\_\_\_\_
- ☒ Inspect Firecontrol Insert for any signs of cracking or other failure. OK
- ☐ Other items of note: \_\_\_\_\_
- ☒ Torque Takedown Screws @ Reassembly: SPEC- Frt- 75 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1216

Remington Confidential

ET21837