

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Extruded Receiver "Magnum Caliber"

Project: 241314

TLW #: TLW1689

Date: 3 11 05

Gun Test # A-31

S/N 71202744

Round Level: 1729

Inspector: B. LEE

☒ Measure Headspace mint. 006

☒ Check Takedown Screw Torque @ Disassembly: Frt 5, Center 5, Rear 10

☒ Sear Engagement: 1<sup>st</sup>. .0306 2<sup>nd</sup>. .0304 3<sup>rd</sup>. .0295 Ave. .0301 spec- .025" to .030"

☐ Reset Sear Engagement if Required: 1<sup>st</sup>. 2<sup>nd</sup> 3<sup>rd</sup>. Ave.

☒ Trigger Pull: 1<sup>st</sup>. 5.489 2<sup>nd</sup>. 5.834 3<sup>rd</sup>. 4.921 Ave. 5.071 spec- 4.5 lb. to 6 lb.

☐ Reset Trigger Pull if Required: 1<sup>st</sup>. 2<sup>nd</sup> 3<sup>rd</sup>. Ave.

☒ Inspect Firecontrol Insert for any signs of cracking or other failure. OK

☐ Other items of note:

☒ Torque Takedown Screws @ Reassembly: SPEC- Frt- 75 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1216

Remington Confidential

ET22003