

TLW 1216ZProject No. 241314**EXTENDED JAR-OFF TESTING**

Firecontrol No. A-14 Firecontrol Type: standard Date: 9/12/03
Dry Cycles/Rounds Completed: _____ Stock Type SYN Engagement at Start _____
Model No. m/710 Serial No. 71126540 Engagement at End _____
Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____
Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/BL

Additional Notes and Comments

83

PERFORM TESTING IN ITS ENTIRETY OR UNTIL THE GUN FAILS.**IF A GUN FAILS, FINISH DROPPING ALL ORIENTATIONS AT THAT HEIGHT, THEN STOP.***Specifications for Extended Jar-Off Test:*

Jar-Off Test: 6, 18, 24, 36 & 48-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop, fire Primed Case to verify firearm will still function.

all drops (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked position for all six orientations of the Jar-Off Test

TLW 1216ZProject No. 241314

A-14

EXTENDED JAR-OFF TESTING

6 INCH EXTENDED JAR- OFF TEST

Engagement before 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement before 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 6"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up:	Pass _____	Fail _____
Barrel Vertical, Muzzle Down:	Pass _____	Fail _____
Barrel Horizontal, Left side of Stock Up:	Pass _____	Fail _____
Barrel Horizontal, Right side of Stock Up:	Pass _____	Fail _____
Barrel Horizontal, Bottom of Stock Up:	Pass _____	Fail _____
Barrel Horizontal, Bottom of Stock Down:	Pass _____	Fail _____

Engagement after 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement after 6"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 6"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

18 INCH EXTENDED JAR- OFF TEST

9-18-03

Engagement before 18"- 1. .0206, 2. .0203, 3. .0203 Avg. .0204

Trigger Movement before 18"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 18"- 1. 4.150, 2. 4.099, 3. 4.096, 4. 4.088, 5. 4.093, Avg. 4.105Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up:	Pass ☒	Fail _____
Barrel Vertical, Muzzle Down:	Pass ☒	Fail _____
Barrel Horizontal, Left side of Stock Up:	Pass ☒	Fail _____
Barrel Horizontal, Right side of Stock Up:	Pass ☒	Fail _____
Barrel Horizontal, Bottom of Stock Up:	Pass ☒	Fail _____
Barrel Horizontal, Bottom of Stock Down:	Pass ☒	Fail _____

Engagement after 18"- 1. .0202, 2. .0204, 3. .0208 Avg. .02046

Trigger Movement after 18"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 18"- 1. 3.530, 2. 3.636, 3. 3.582, 4. 3.654, 5. 3.839, Avg. 3.648

TLW 12162Project No. 241314

A-14

EXTENDED JAR-OFF TESTING**24 INCH EXTENDED JAR-OFF TEST**Engagement before 24"- 1. .0202, 2. .0204, 3. .0208 Avg. .02046

Trigger Movement before 24"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 24"- 1. 3.940, 2. 4.088, 3. 4.008, 4. 4.047, 5. 4.066, Avg. 4.028Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up:	Pass ☒	Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass ☒	Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass ☒	Fail _____	_____

Engagement after 24"- 1. .0206, 2. .0204, 3. .0206 Avg. .02053

Trigger Movement after 24"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 24"- 1. 4.296, 2. 4.771, 3. 4.664, 4. 5.007, 5. 4.563, Avg. 4.660**36 INCH EXTENDED JAR-OFF TEST**

Engagement before 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement before 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 36"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up:	Pass _____	Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass _____	Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass _____	Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass _____	Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass _____	Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass _____	Fail _____	_____

Engagement after 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Movement after 36"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 36"- 1. _____, 2. _____, 3. _____, 4. _____, 5. _____, Avg. _____

ET22323

TLW 1216 Z

Project No. 241314

A-14

EXTENDED JAR-OFF TESTING

48 INCH EXTENDED JAR-OFF TEST

Engagement before 48"- 1. .0206, 2. .0204, 3. .0206 Avg. .02053

Trigger Movement before 48"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull before 48"- 1. 4.092, 2. 4.062, 3. 4.134, 4. 3.962, 5. 4.113, Avg. 4.073

Orientation

ISS Unlocked

Comments

Barrel Vertical, Muzzle Up:

Pass ☒ Fail _____

Barrel Vertical, Muzzle Down:

Pass ☒ Fail _____

Barrel Horizontal, Left side of Stock Up:

Pass ☒ Fail _____

Barrel Horizontal, Right side of Stock Up:

Pass ☒ Fail _____

Barrel Horizontal, Bottom of Stock Up:

Pass ☒ Fail _____

Barrel Horizontal, Bottom of Stock Down:

Pass ☒ Fail _____

BOLT HANDLE BROKE (REPLACED)

83

Engagement after 48"- 1. .0205, 2. .0208, 3. .0207 Avg. .02066

Trigger Movement after 48"- 1. _____, 2. _____, 3. _____ Avg. _____

Trigger Pull after 48"- 1. 3.913, 2. 3.966, 3. 3.972, 4. 3.961, 5. 3.909, Avg. 3.944