

GUN # A-2

SERIAL # 71126307

CAL 300 WIN MAG

DAT # 1 M 710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216

PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
SW/BL	7/21/03	Weight	8.427 TLW 1216 AM		
SW/BL	7/21/03	Head Space	Min +.001		TLW1216A
SW/BL	7/21/03	Head Space	Shoulder Gauge .321 Will not close up		TLW1216A
SW/BL	7/21/03	Firing Pin Indent	.020 - .021 - .022 Avg. .021		TLW1216B
SW/BL	7/22/03	Balance Point	From Butt Pad 19.5"		TLW1216AN
SW/BL	7/22/03	Trigger Pull	4.666, 4.727, 4.601 Avg 4.664		TLW1216F
SW/BL	7/22/03	Sear/Trigger Engagement	.0290, .0296, .0290 Avg. .0292		TLW1216E
SW/BL	7/22/03	Sear Lift	.0235		TLW1216E
SW/BL	7/22/03	Reset Sear/Trigger	Engagement .0246, .0245, .0247 Avg. .0246		TLW1216E
SW/BL	7/22/03	Reset Trigger Pull	4.428, 4.447, 4.540 Avg. 4.471		TLW1216F
SW/BL	7/22/03	Firing Pin Head/Sear Engagement	.061		TLW1216E
SW/BL	7/23/03	Safety ON Forces	5.005, 5.180, 5.205 Avg 5.130		TLW1216G
SW/BL	7/23/03	Safety OFF Forces	2.245, 2.068, 2.105 Avg 2.138		TLW1216G
SW/BL	7/24/03	Bolt Lift	15.94, 17.12, 17.22 Avg 16.76		TLW1216H
SW/BL	7/24/03	Bolt Close	6.18, 5.54, 5.716 Avg 5.82		TLW1216H
SW/BL	7/24/03	Bolt Lift w/Dummy	16.04, 16.00, 16.08 Avg 15.57		TLW1216H
SW/BL	7/24/03	Bolt Close w/Dummy	7.14, 5.68, 6.08 Avg 6.30		TLW1216H
SW/BL	7/25/03	Magazine Spring Force	Gauge 0.200 1.980 - 1.880 - 1.880 Avg 1.913		TLW1216I
			Gauge 1.0" 4.045 - 4.740 - 4.770 Avg 4.518		
SW/BL	7/29/03	Magazine Capacity Test	Pass - Weak Ejection		TLW1216D
SW/BL	7/29/03	Check Eject System	Pass		TLW1216AI
SW/BL	7/29/03	Twist Rate	1 Turn 10" + .25		TLW1216N
SW/BL	7/30/03	Bore diameter	Spec .300/.301 Dimension .300		TLW1216L
SW/BL	7/30/03	Chamber Cast/measurements	See Spread Sheet		TLW1216K
SW/BL	7/30/03	Groove diameter	Spec .308/.309 Dimension .3093		TLW1216M
SW/BL	8/6/03	Proof Test (Hammer bolt up & back, signs of locking)	2nd case stuck in bolt, ejector stuck back.		TLW1216B
SW/BL	8/6/03	Head Space After Proof Min (See Proof Test)			TLW1216C
SW	8/7/03	Took Bolt From B-1 and Put in A-2			
SW/BL	8/7/03	Head Space	Min +.001		TLW1216A
SW/BL	8/7/03	Proof Test	Hammer bolt Back		TLW1216B
SW/BL	8/7/03	Head Space After Proof Min +.001			TLW1216C
SW/BL	8/8/03	Basic Jack Function Test	0 malfunctions		TLW1216P
Jeff C	8/12/03	Basic Shoulder Function Test	0 Malfunctions		TLW1216Q
				200	202
				20	222

Logform

Confidential - Subject to Protective Order

Williams v. Remington

ET22570