

GUN # A-13

DAT # 1 M / 710 MAGNUM PRODUCTION RECEIVER INSERT

TRACKING # TLW1216

PROJECT #241314

SERIAL # 71126321

CAL 300 WIN MAG

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS RDS. FIRED	AT START-0 TOTAL RDS.
SW/BL	7/21/03	Handspace	Min +.005		TLW1216A
SW/BL	7/21/03	Handspace	Shoulder Gauge .721 Will not close up		TLW1216A
SW/BL	7/21/03	Firing Pin Indents	.019-.019 .020 Avg. .0193		TLW1216B
SW/BL	7/22/03	Trigger Pull	5.215 5.264, 5.248 Avg 5.242		TLW1216F
SW/BL	7/22/03	Sear Trigger Engagement	.0282, .0282, .0280 Avg. .02813		TLW1216E
SW/BL	7/22/03	Sear Lift	.0218		TLW1216E
SW/BL	7/22/03	Reset Sear Trigger Engagement	.0251, .0249, .0249 Avg. .02496		TLW1216E
SW/BL	7/22/03	Trigger Pull	5.809, 5.866, 4.942 Avg 5.072		TLW1216F
SW/BL	7/22/03	Firing Pin Head/Sear Engagement	.063		TLW1216E
SW/BL	7/23/03	Safety ON Forces	4.845, 4.810, 4.995 Avg 4.880		TLW1216G
SW/BL	7/23/03	Safety OFF Forces	2.220, 2.035, 3.075 Avg 2.107		TLW1216G
SW/BL	7/24/03	Bolt Lift	16.16, 16.64, 16.22 Avg. 16.34		TLW1216H
SW/BL	7/24/03	Bolt Close	6.02, 5.98, 5.32 Avg. 5.77		TLW1216H
SW/BL	7/24/03	Bolt Lift w/Dummy	16.48, 16.06, 16.02 Avg. 16.18		TLW1216H
SW/BL	7/24/03	Bolt Close w/Dummy	6.24, 6.19, 6.24 Avg. 6.22		TLW1216H
SW/BL	7/25/03	Magazine Spring Force	gauge 0.200 1.705-1.760-1.765 Avg. 1.703		TLW1216I
			gauge 1.0 4.375-4.950-5.385 Avg. 4.903		
SW/BL	7/29/03	Magazine Capacity Test	pass weak ejection		TLW1216D
SW/BL	7/29/03	Check FSS System	PASS		TLW1216A
SW/BL	7/29/03	Twist Rate	1 Turn 10"		TLW1216A
SW/BL	7/30/03	Bore diameter	Spec .300/301 Dimension .300		TLW1216L
SW/BL	8/6/03	Proof Test	Hammer bolt break		TLW1216B
SW/BL	8/6/03	Handspace After Proof	Min +.006		TLW1216C
SW/BL	8/20/03	Inspection	Checked stock for cracks, stock has cracks		TLW1216
SW/BL	9/11/03	SAAMI JAR OFF TEST	PASS		TLW1216X
SW/BL	9/12/03	SAAMI ROTATION TEST	PASS		TLW1216Y
SW/BL	9/12/03	SAAMI DROP TEST	PASS		TLW1216W
SW/JS	9/18/03	Extended 18" JAR-Off Test	PASS		TLW1216Z
SW/JS	9/19/03	EXTENDED 24" JAR-Off TEST	PASS		TLW1216Z
SW/JS	9/19/03	EXTENDED 48" JAR-Off TEST	FAIL		TLW1216Z
SW	9/25/03	Handspace	Min +.6 OK		
BL/JSins	10/22/03	Scope mount / Scope	used Torque wrench to torque mount at 25 in Lbs. / Scope 40 in Lbs.		
B-Lee/JSins	10/23/03	Accuracy #1	5-5 shot groups - 5 failing mg shots	30	37

Logform

Confidential - Subject to Protective Order

Williams v. Remington

ET22583