

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 EXTRUDED RECEIVER

Project: 241230

Rifle: A-11

TLW #: TLW1530

Date: 8 / 16 / 04

Inspector: SW

Round Level: 241

☒ Measure Headspace Min +.002

☒ Sear Engagement: 1<sup>st</sup>. .0338 2<sup>nd</sup>. .0340 3<sup>rd</sup>. .0339

Ave. .0339 spec. .020" to .025"

☐ Reset Sear Engagement if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_

Ave. \_\_\_\_\_

☒ Trigger Pull: 1<sup>st</sup>. 4.639 2<sup>nd</sup>. 4.620 3<sup>rd</sup>. 4.768

Ave. 4.676 spec. 4 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1<sup>st</sup>. \_\_\_\_\_ 2<sup>nd</sup>. \_\_\_\_\_ 3<sup>rd</sup>. \_\_\_\_\_

Ave. \_\_\_\_\_

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs normal wear

☒ Inspect stock for any signs of cracking or other failure. OK

☐ Other items of note: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

TLW1216

Remington Confidential

ET22944