

TLW \_\_\_\_\_

Project No. 241095**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**

Gun  
 Firearm No. B27 Firecontrol Type: Standard Date: 12/1/00  
 Dry Cycles/Rounds Completed: \_\_\_\_\_ Stock Type Syn Engagement at Start \_\_\_\_\_  
 Model No. 710 Serial No. 71001724 Engagement at End \_\_\_\_\_  
 Trigger Pull at Start of Test (1) \_\_\_\_\_ (2) \_\_\_\_\_ (3) \_\_\_\_\_ (4) \_\_\_\_\_ (5) \_\_\_\_\_ (6) \_\_\_\_\_  
 Average Trigger Pull at Start of Test: \_\_\_\_\_ Std. Dev. of Trigger Pull at Start of Test: \_\_\_\_\_  
 Trigger Pull at End of Test (1) \_\_\_\_\_ (2) \_\_\_\_\_ (3) \_\_\_\_\_ (4) \_\_\_\_\_ (5) \_\_\_\_\_ (6) \_\_\_\_\_  
 Average Trigger Pull at End of Test: \_\_\_\_\_ Std. Dev. of Trigger Pull at End of Test: \_\_\_\_\_

Tester Initials: SW + JW

Additional Notes and Comments

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt  
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in  
 Chamber, Magazine loaded to capacity with Dummy Rounds.  
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked  
 position for all six orientations of the Jar-Off Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail _____	_____

TLW \_\_\_\_\_

Project No. \_\_\_\_\_

## S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

### *SAAMI Specifications for Standard Drop Test:*

**Drop Test:** 48-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt  
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case  
 in Chamber, Magazine loaded to capacity with Dummy Rounds.  
 After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the  
 ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass _____ Fail _____	
Barrel Vertical, Muzzle Down:	Pass _____ Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass _____ Fail _____	
Barrel Horizontal, Right side of Stock Up:	Pass _____ Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass _____ Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass _____ Fail _____	

### *SAAMI Specifications for Standard Rotation Test:*

**Rotation Test:** Rest Firearm on the Butt end and allow Firearm to fall  
 Drop onto 1" thick 85 durometer (Shore A) Rubber Matt  
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case  
 in Chamber, Magazine loaded to capacity with Dummy Rounds.  
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the  
 ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass _____ Fail _____	
Firearm Vertical, Drop so right side of Stock is Up:	Pass _____ Fail _____	

Notes: (continue on back of sheet if necessary)

---



---



---

Tester's Initials \_\_\_\_\_