Remington Arms Company Inc. Research & Development Technical Center 315 West Ring Road Elizabethtown, KY 42701

- Rifle serial number
- Record and note any headspace growth and the corresponding round level.
- Record significant gas leakage and/or firearm damage.
- Record any case damage or other ammunition related malfunctions.
- Record any damage to the firearm resulting from the proof test. Document with Photographs as necessary.

TLW0300G - Re-Measure Headspace after Proof

All test samples will be re-measured for headspace after proof and before being tested in either the fack or shot from the shoulder. The chamber, bolt face & locking block/locking notch will be inspected for the presence of dirt or debris. If dirt or debris that could affect headspace measurement is present then these areas of the firearm will be thoroughly cleaned before using the gauges.

Method:

• The headspace measurement taken prior to the proof test should be less than min. + .005". If, after proof, the growth of the headspace is more than + .002" from the pre-proof condition, then stop and review the results with the test manager before continuing to the next phase of the test.

- In no case should the measurement for headspace after initial proof test be greater than min.+007" for a new firearm.
- If at any time during the test program the headspace exceeds a maximum of Min. + .009" do not continue to fire the rifle, tag the gun with a label reading "Do Not Shoot This Firearm Exceeds Maximum Allowable Headspace" and return the firearm to the Test Manager for disposition.

Data Required:

I.R.Snedeker	Page 11 of 51	5:25 PM
11/02/00		

Remington Confidential

TLW0300

Revision # 3

ET53512

Confidential - Subject to Protective Order Williams v. Remington