

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Method:

- Condition the firearm and 100 rounds of ammunition of climatic chamber for at least 6 hours at a temperature of -20 degrees F.
- Test each firearm after removing from the chamber as follows:
- Fire 20 rounds of ammunition. Return the firearm to the chamber. Wait 2 hours and repeat procedure until all 100 rounds have been fired.
- Do not perform maintenance during the 100 round cycle.
- Cycle the safety from fire to safe every 5 rounds.
- After 100 rounds have been fired through the firearm, disassemble, thoroughly inspect, clean and lubricate.

Data Required:

- Record temperature and exposure times
- Record all malfunctions.
- Record damage noted during inspection

TLW0407A1 - Heat & Humidity Function Test:Method:

- Shoot the firearm after removing from the environmental test cabinet in the long range.
- Store the gun and ammunition for a minimum of six hours at a temperature of +100°F and 80-90% Relative Humidity.
- Test each firearm after removing from the chamber as follows:
- Fire 20 rounds of ammunition. Return the firearm to the chamber. Wait 2 hours and repeat procedure until all 100 rounds have been fired.
- Do not perform maintenance during the 100 round cycle.
- Cycle the safety from fire to safe every 5 rounds.
- After 100 rounds have been fired through the firearm, disassemble, thoroughly inspect, clean and lubricate.

J.R.Snedeker

Page 31 of 32

10:05 AM

05/24/06

TLW0407

Remington Confidential

Revision # 2