

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

System failures are defined as failures of a major nature, the extent of which would require specialized tooling or methods to repair not normally available to the average gun owner. Such a repair would be most likely made by a qualified gunsmith or by return to the factory.

This Endurance Test will be shot in the test jacks and the testers will use gloves for protection. The covers on the "belly-protectors" will be down and in-place for each test shot. Careful monitoring of each test gun is essential to evaluate the malfunction rate for each firearm. The standard Remington test jacks will be used for all jack-related testing.

Each rifle will be shot, using a variety of Centerfire ammunition comprised of light, medium and heavy bullets. In addition, ammunition from the three major manufacturers (Remington, Winchester and Federal) of Centerfire ammunition shall be included in the mix.

Each rifle will be shot no more than 20 rounds before being put aside for cooling. Compressed air applied to the inside of the chamber will be an acceptable method to assist in the cool-down process.

The S.A.A.M.I. recommendation for the minimum acceptable malfunction rate for a bolt action rifle is a malfunction rate of < 2%. In this case, if the overall malfunction rate average for the test samples is > 2%, the DAT test will be stopped and the guns returned to Design for modification and improvement before being re-submitted for DAT. If the overall average malfunction rate is < 2% but one of the firearms is significantly greater than 2% malfunction rate, the test may continue with the other nine test samples while Design attempts to fix the problem with malfunctioning gun. After repair, this gun will again be required to pass the 200 round jack function test at < 2% malfunction rate. If the gun passes these criteria it will then be re-introduced into the Endurance test. It is important that total endurance rounds on the gun include any rounds that are put through the gun for re-test purposes.

The test will be performed according to Remington's standard endurance test procedures for centerfire rifle. Pyramid for this test will be ten rifles to 1,000 rounds, six rifles to 2,000 rounds, three rifles to 5,000 rounds and one rifle to 10,000 rounds.

Record all instances of malfunctions and failures, and replace parts when they become unserviceable noting the round level when they were replaced.

After every 100 rounds one live round will be extracted and ejected from the chamber to check on live round ejection. The ejected round will then be re-inserted into the chamber and fired to help keep the endurance round count accurate.

J.R. Snedeker

Page 36 of 62

03/31/00

Remington Confidential

Revision #2