

G680137C

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

BM FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6801376

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6801376

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-14-08	S.P.D.
430	ASSEMBLE TO STOCK		10-14-08	SP
440	PROOF		10-14-08	S.P.D.
460	CHECK HEADSPACE		10-14-08	S.P.D.
470	DIS-ASSEMBLE ACTION		10-14-08	S.P.D.
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX	10-15-08	RT
475	DRILL AND TAP SIGHT HOLES		10-15-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR	10/17/08	(S)
490	MAGNAFLUX BOLT		10/17/08	NR
500	ROLLMARK CALIBER		10/17/08	RT
520	GOFF BLAST BBL / REC		10/20/08	DB
542	APPLY COATINGS (BARREL ACTION)		10-23-08	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-23-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-23-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-23-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-10-08	RT
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>2.5</u> <u>3.0</u> <u>3.0</u>	11-18-08	290
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>4.0</u> <u>4.0</u> <u>4.0</u>	11-18-08	290
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	11-18-08	290
	J) ASSEMBLE STOCK		11-10-08	RTZ
	K) ASSEMBLE SWIVEL STUDS		11-18-08	290
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-11-08	TL
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-18-08	290
670	FINAL INSPECTION A) HEADSPACE		11-18-08	290
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.65</u> <u>2.70</u> <u>2.70</u> <u>2.66</u> <u>2.60</u>	11-11-08	TL
	C) FUNCTION		11-18-08	290
690	PACK		12-2-08	TL

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE 10-31-08

TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	241	243		268	
PULL #2	241	245		275	
PULL #3	233	251		268	
PULL #4	236	256		272	
PULL #5	233	256		274	
TOTAL	1184	1251		1357	
AVERAGE	236	250		271	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	336	336		
PULL #2	329	336		
PULL #3	334	332		
PULL #4	341	337		
PULL #5	350	338		
TOTAL	1690	1679		
AVERAGE	338	335		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	432	429		431
PULL #2	429	430		435
PULL #3	425	436		434
PULL #4	420	436		427
PULL #5	425	430		425
TOTAL	2131	2161		2152
AVERAGE	426	432		430