

CONFIDENTIAL

Remington Arms Company Inc.  
RESEARCH & DEVELOPMENT TECHNICAL CENTER  
315 WEST RING ROAD  
ELIZABETHTOWN, KY 42701

**TLW0407C – Packaging Test**

This section of the test will be an intentional abuse of the product while in the shipping carton. The sample firearm will be packaged according to ship level criteria and dropped from a height of four feet onto a tile floor. The external packaging material will be examined for damage and then the packaging will be opened. Interior packing material integrity will be examined and assessed for damage. The firearm will be removed from the packaging and examined for damage, nicks, or other cosmetic degradation. This sequence will be repeated six times using new packaging material for each sequence and each time the product is dropped it will be on a different side so during the course of the test each of the six sides will be tested. The firearm product itself may be repaired or replaced as necessary to permit the test to continue. This portion of the test will be considered informational only as the test attempts to simulate the effects of the product being pushed from the back of a tractor-trailer and allowed to fall to the ground. This would be considered a worst-case packaging drop abuse.

**HEADSPACE AND PROOF - TLW0407E THROUGH TLW0407G:**

**TLW0407E – Measure Headspace**

All test samples will be measured for headspace before being tested in either the jack or shot from the shoulder. The chamber, bolt face & locking lugs will be inspected for the presence of dirt or debris. If dirt or debris that could affect headspace measurement is present then these areas of the firearm will be cleaned before using the gauges.

**Method:**

The graduated headspace gauges based on Remington chamber dimensions (Ref: Remington Gauge Drawing # 41560 A, B, C & D) will be used and the headspace measurements will be recorded to the nearest .001” increment as indicated by the gauge. The .270 Remington chamber drawing LB-154 will be used for chamber dimensions.

The headspace measurements will be recorded to the nearest .001” increment as indicated by the gauge.

J.R.Snedeker

9:47 AM 05/24/06

TLW0407

Remington Confidential

Revision # 2