

UPC



C6702783

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # C6702783
8 Oct 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.328667$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $-.301$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.445671$

THE AMR FOR THIS RIFLE IS: 1.048

CENTROIDAL DISTANCES

0 TO 1	.317907
1 TO 2	.368751
1 TO 3	.248751

3 1 + <----POA
2


PATTERN #: 1

POA TO CENTROID: .318
 MIN RADIUS : .250
 MEAN RADIUS : .746
 MAX RADIUS : 1.109
 CENTROID X : -.236
 CENTROID Y : -.213

8 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702783

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.57

2

VS= 1.67

4

GS= 2.06

5


PATTERN #: 2

POA TO CENTROID: .648
 MIN RADIUS : .226
 MEAN RADIUS : 1.336
 MAX RADIUS : 3.276
 CENTROID X : -.295
 CENTROID Y : -.577

8 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702703

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.84
 VS= 4.30
 GS= 4.56

1
 2
 4


PATTERN #: ☐ 3 ☐

POA TO CENTROID: .469
 MIN RADIUS : .258
 MEAN RADIUS : 1.061
 MAX RADIUS : 2.203
 CENTROID X : -.455
 CENTROID Y : -.113

8 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/C6702783

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 3.67
 VS= 1.36
 GS= 3.92

2
 3
 3

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # C 670 2783

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>5</u> <u>5</u> <u>5</u>	10-8-97	CR
CONT.	G) SAFETY OFF FORCE	<u>2</u> <u>2</u> <u>2</u>	10-8-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>1021</u> <u>1022</u> <u>1022</u>	10-8-97	CR
	J) ASSEMBLE STOCK		9-28-97	CR
	K) ASSEMBLE SWIVEL STUDS		10/16/97	RP
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		9-29-97	CR
	M) IRON SIGHT ALIGNMENT		9-29-97	CR
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		9-29-97	CR
640	GALLERY TEST AND TARGET	L 85 R 65	10-8-97	P.B.
	A) MALFUNCTIONS		10-8-97	P.B.
	B) PIERCED PRIMERS		10-8-97	P.B.
645	INSPECT FOR LIVE AMMO		10-8-97	1A
655	FINAL INSPECTION A) HEADSPACE		10/16/97	RP
	B) TRIGGER PULL	<u>2.36</u> <u>2.38</u> <u>2.39</u> <u>2.42</u> <u>2.41</u>	10-13-97	CR
	C) FUNCTION		10/16/97	RP

SWS TRIGGER PULL TEST

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C-6702783

DATE 9-17-97

TESTER TM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.56	2.52	2.65	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.52	2.55	2.76	
PULL #3	2.54	2.54	2.71	
PULL #4	2.56	2.49	2.34	
PULL #5	2.54	2.59	2.76	
TOTAL	12.72	12.69	13.22	
AVG.	2.544	2.538	2.64	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.02	3.11	
PULL #2	3.03	3.06	
PULL #3	3.05	3.02	
PULL #4	3.04	3.02	
PULL #5	3.10	2.96	
TOTAL	15.24	15.17	
AVG.	3.048	3.034	


	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.04	4.16		4.16
PULL #2	4.09	4.05		4.24
PULL #3	4.09	4.09		4.18
PULL #4	4.19	4.19		4.22
PULL #5	4.21	4.19		4.14
TOTAL	20.62	20.68		20.94
AVG.	4.12	4.13		4.18

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Do Not Use

Do Not Use

SERIAL NO.



C6702783

ORDER 25705
MODEL 700™ M24
UPC



011 47700 25705 1

ORDER 25705
MODEL 700™ M24
UPC



011 47700 25705 1

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
item.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee

SERIAL NO.
C6702783

46

ORDER NO.
25705

01XR

5705 C6702783