

G 6288234

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

Remington®

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

28

Made in Ilion, NY Reg. U.S. Pat. & tm. Off. Marca Registrada Marque Deposee.

SERIAL NO.
G6288234

ORDER NO.
25716

07EX



5716 G6288234

ORDER

25716

M/24 7.62 NATO S.W.S. (COMPLETE SYST

UPC



ORDER

25716

M/24 7.62 NATO S.W.S. (COMPLETE SYST


UPC



M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

— INSTRUCTION BOOK 3518

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6288234

UPC



28 FORM

M-24
INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G6288234

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		11-12-03	RTZ
600	PROOF		8-12-03	Ac
607	CHECK HEADSPACE	MAGNA-FLUX INSPECTED	8-12-03	Ac
610	DIS-ASSEMBLE GUN		11-12-03	RTZ
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	AUG 14 2003 OPERATOR <i>BR</i>		
615	ROLLMARK CALIBER		8-15-03	SB
617	DRILL AND TAP SIGHT HOLES		8-13-03	TRW
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY		9-29-03	RW
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		9-29-03	RW
	C) INSPECT EJECTOR HOLE FOR CHAMFER		9-29-03	RW
	D) OIL FIRING PIN ASSEMBLY		9-29-03	RW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>616s</u> <u>616s</u> <u>616s</u>	10-1-03	AC
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>316s</u> <u>316s</u> <u>316s</u>	10-1-03	AC
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.022</u> <u>.022</u> <u>.022</u>	10-1-03	AC
	J) ASSEMBLE STOCK		9-29-03	RW
	K) ASSEMBLE SWIVEL STUDS		10-1-03	RW
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		9-29-03	RW
	M) IRON SIGHT ALIGNMENT		9-29-03	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		9-29-03	RW
640	GALLERY TEST AND TARGET	PASS FAIL	9-30-03	L
	MALFUNCTION	CORRECTION	9-30-03	L
	MALFUNCTION	CORRECTION	9-30-03	L
	MALFUNCTION	CORRECTION	9-30-03	L
	MALFUNCTION	CORRECTION	9-30-03	L
645	INSPECT FOR LIVE AMMO		9-30-03	L
655	FINAL INSPECTION A) HEADSPACE		10/1/03	RW
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.37</u> <u>2.36</u> <u>2.59</u> <u>2.66</u> <u>2.44</u>	10-1-03	DA
	C) FUNCTION		10/1/03	RW
660	PACK		10-4-03	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

SERIAL NO. _____

DATE 8-4-03

TESTER TRW

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.45	2.62		2.71	
PULL #2	2.50	2.56		2.73	
PULL #3	2.43	2.67		2.76	
PULL #4	2.44	2.66		2.80	
PULL #5	2.47	2.65		2.75	
TOTAL	12.29	13.16		13.75	
AVERAGE	2.45	2.63		2.75	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.40	3.38		
PULL #2	3.34	3.16		
PULL #3	3.03	3.30		
PULL #4	3.28	3.49		
PULL #5	3.15	3.39		
TOTAL	16.20	16.72		
AVERAGE	3.24	3.34		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.23	4.17		4.41
PULL #2	4.27	4.23		4.06
PULL #3	4.37	4.02		4.26
PULL #4	4.25	4.10		4.37
PULL #5	4.23	4.21		4.33
TOTAL	21.35	20.73		21.43
AVERAGE	4.27	4.14		4.28

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6288234.___0
FILE DATE AND TIME: 09/30/2003 06:42

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES


ERROR - NOT POSSIBLE TO REPORT SWS STATS ON DATA
WHERE TOTAL TARGETS ARE NOT EQUAL TO FIVE

mean .953

SERIAL NUMBER: G6288234. __0
TARGET NUMBER: 1
FILE DATE: 09/30/2003
FILE TIME: 06:42

POINT#	X	Y
1:	0.687	-0.228
2:	-0.071	-0.045
3:	-0.934	0.068
4:	-1.440	0.444
5:	1.361	0.372

X CENTROID: -0.079
Y CENTROID: 0.122
POA TO CENTROID: 0.146
HORZ SPREAD: 2.801
VERT SPREAD: 0.672
GROUP SPREAD: 2.802
MIN RADIUS: 0.167
MAX RADIUS: 1.462
MEAN RADIUS: 0.945
IN 1 IN DIAMETER: 1
IN 2 IN DIAMETER: 3
in 3 IN DIAMETER: 5




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6288234. __0
TARGET NUMBER: 2
FILE DATE: 09/30/2003
FILE TIME: 06:42

POINT#	X	Y
1:	1.093	-0.108
2:	0.221	-1.002
3:	-0.222	-0.390
4:	0.034	0.612
5:	-0.346	1.611

X CENTROID: 0.156
Y CENTROID: 0.145
POA TO CENTROID: 0.213
HORZ SPREAD: 1.439
VERT SPREAD: 2.613
GROUP SPREAD: 2.674
MIN RADIUS: 0.483
MAX RADIUS: 1.550
MEAN RADIUS: 0.961
IN 1 IN DIAMETER: 1
IN 2 IN DIAMETER: 3
in 3 IN DIAMETER: 4



TARGET APPROX 1/2 SCALE