

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

INTRODUCTION:4

INITIAL TESTS, MEASUREMENTS AND INSPECTIONS:5

VISUAL EXAMINATION, PACKAGING AUDIT, PACKAGING TEST - TLW0300A THROUGH TLW0300C:.....5

TLW0300A - Visual Examination: 5

TLW0300B - Packaging Audit:..... 5

TLW0300C - Packaging Test: 6

HEADSPACE AND PROOF - TLW0300E THROUGH TLW0300G:.....6

TLW0300E - Measure Headspace: 6

TLW0300F - Proof Test: 7

TLW0300G - Re-Measure Headspace after Proof:10

FORCES - TLW0300H THROUGH TLW0300Q AND TLW0300AT:.....11

TLW0300H - Measure Firing Pin Indent:.....11

TLW0300I - Measure Sear/Trigger Engagement and Sear Lift:13

TLW0300J - Measure Trigger Pull Forces:14

TLW0300K - Measure Safe On/Off Forces:14

TLW0300L - Measure Bolt Lift and Bolt Closing Forces:15

TLW0300M - Measure Magazine Spring Force:16

TLW0300N - Measure Firing Pin Head / Sear Engagement:17

TLW0300O - Bolt Stop Function Check:18

TLW0300P - Function Check of JSS System:19

TLW0300Q - Magazine Box Weld Strength Test:20

TLW0300AT - Perform Bare Sighting Using Bushnell Scope:21

GUN CHARACTERISTICS - TLW0300R THROUGH TLW0300S:22

TLW0300R - Balance Point - "System (Includes Scope and Mount Rails)":22

TLW0300S - Balance Point - "Rifle Only (Without Scope, Mount Rails and Iron Sights)":23

FIREARMS MEASUREMENTS - TLW0300T THROUGH TLW0010X:24

TLW0300T - Chamber Cast:24

TLW0300U - Bore Diameter:24

TLW0300V - Groove Diameter:25

TLW0300W - Twist Rate (30-06):25

TLW0300X - Magazine Capacity Test:25