

Jason Spradlin

From: campbelln@co.oakland.mi.us
Sent: 10/26/2005 05:22:09 PM
To: Spradling, Jason
CC:
BCC:
Subject: RE: Remington 700 rifle

Mr. Spradling,

thanks for the response, Our team appreciates it. I am forwarding your email address to one of team members who is expericeing some trigger problems . He can explain to you what he is going thru to get it fixed. THANKS AGAIN!!!!

Al

--- Original message ---

>Date: Wed, 26 Oct 2005 14:44:53 -0400
>From: "Spradling, Jason" <Jason.Spradling@remington.com>
>Subject: RE: Remington 700 rifle
>To: <campbelln@co.oakland.mi.us>
>
>Al:
>
>I'm glad your trigger is working better for you now.
>
>When you "reset" your trigger, what you're actually doing is re-cocking
>the firing pin. As you do this, the firing pin head has to re-engage
>the sear. Sometimes, you have to move the bolt rearward a few
>thousandths of an inch for this to happen correctly. This is completely
>normal and will not present a problem when you fire the rifle as you
>will be cycling the bolt to complete the extract/eject/load cycles.
>When you dry fire for practice, however, it may not re-cock completely
>every time without some rearward movement in the bolt.
>
>To answer your second question, the safety really doesn't "wear in" to
>the point that it's smoother or easier to manipulate. It uses a detent
>spring and detent ball to provide that audible click and the
>corresponding positive engagement. We designed it this way for several
>reasons. It prevents the safety from being disengaged unintentionally
>and the audible click alerts the shooter that the safety has been
>disengaged. A simple flip of the thumb against the safety

arm should
>disengage it easily enough. If it takes substantial effort
to move the
>safety arm, it may be possible to adjust the engagement of
the detent
>spring and ball.
>
>If you have more questions, please let me know ASAP.
Thanks.
>
>Jason
>
>-----Original Message-----
>From: campbelln@co.oakland.mi.us
[mailto:campbelln@co.oakland.mi.us]
>Sent: Thursday, October 20, 2005 8:30 PM
>To: Spradling, Jason
>Subject: Remington 700 rifle
>
>Mr. Spradling,
>
>I just got my rifle back from Williams gun sight and the
>trigger pull is now awesome. THANKS!!!!!! I have another
>technical question(s) for you...with the rifle bolt closed
>and the trigger is not set, If I lift the bolt handle as if
>to chamber a round, but dont pull the bolt back, the trigger
>should "re-set" shouldnt it
? I have noticed that mine does
>not always do that. After ten trys, it reset 7 times. The
>three remaining times, it did not. I may be wrong, because I
>just dont know enough about the internal workings of the
>rifle, but I was under the impression that it should re-set
>every time with out pulling the bolt completely back. Like I
>said just curious.
>Second question, if you have time, is...how can I "smooth"
>out the safety. Sometimes it seems as if the safety is hard
>to manipulate. I have approximatley 1500+ rounds thru the
>rifle and thought that it should have smoothed out by now. I
>worked that saftey back and forth a lot and it just doesnt
>seem to get any smoother.
>Seems to me like I need to attend an armor's course, but
that
>probably wont happen till next year.(on a budget with the
>Sheriff's Office)so your advise is greatly appreciated.
>
>
>Thanks a million,
>
>Al
>Oakland County Sheriff's Office
>Special Response Team-Scout/ Sniper Unit
>
>
>FOR THOSE WHO DARE
>
>RESPECT ALL
>
>FEAR NONE
>
>
>This Email has been scanned for Viruses and Spam by an E500
McAfee
>Engine

>
>
>This Email has been scanned for Viruses by an E500 McAfee
Engine

FOR THOSE WHO DARE...

RESPECT ALL...

FEAR NONE...

This Email has been scanned for Viruses and Spam by an E500 McAfee Engine