

Danny:

This is an attempt to provide a simple fix for the current design. There is a change in operational philosophy - the safety now forces the trigger under the sear when you go to the "safe" position, and the safety holds the trigger there.

Advantages:

1. Easily implemented in current mechanism, existing parts can be modified, existing adjustments are unchanged.
2. Use of radial surfaces on pawl and trigger stud insures absence of unwanted off-center loads.
3. Same protection against firing if the trigger is pulled while the safety is taken off.

Disadvantages:

1. Difficult disassembly: Stud must be added to the trigger after assembly, and probably should be loctited.
2. New part may get stuck by dirt. However, it is a safe condition since the trigger can't be pulled even if the pawl is stuck.

Thanks to Dave Schluckebier for sending prints and parts.

Standing by for consultation.

Don Rolph
Don Rolph

5/2/95

2/5/95

ET56360

Danny:

This is an attempt to provide a simple fix for the current design. There is a change in operational philosophy - the safety now forces the trigger under the sear when you go to the "safe" position, and the safety holds the trigger there.

Advantages:

1. Easily implemented in current mechanism, existing parts can be modified, existing adjustments are unchanged.
2. Use of radial surfaces on pawl and trigger stud insures absence of unwanted off-center loads.
3. Same protection against firing if the trigger is pulled while the safety is taken off.

Disadvantages:

1. Difficult disassembly: Stud must be added to the trigger after assembly, and probably should be loctited.
2. New part may get stuck by dirt. However, it is a safe condition since the trigger can't be pulled even if the pawl is stuck.

Thanks to Dave Schluckebier for sending prints and parts.

Standing by for consultation.

Don Rolph
Don Rolph

5/2/95

v/s

ET56360



Confidential - Subject
to Protective Order
Williams v. Remington