

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

M/710 Design Acceptance Test (DAT #1)

Test Plan

Model 710, New Centerfire Rifle

Revision # 2

03/31/00

Remington Confidential

PLAINTIFF'S
EXHIBIT

357

EXHIBIT

55

ET07332

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

APPROVALS.....	5
INTRODUCTION:.....	6
INITIAL TESTS, MEASUREMENTS AND INSPECTIONS:.....	8
HEADSPACE AND PROOF - TLW0010A THROUGH TLW0010C:.....	8
TLW0010A - Measure Headspace.....	8
TLW0010B - Proof Test.....	9
TLW0010C - Re-Measure Headspace after Proof.....	12
FORCES - TLW0010D THROUGH TLW0010K:.....	13
TLW0010D - Measure Firing Pin Indent.....	13
TLW0010E - Measure Scar/Trigger Engagement and Scar Lift.....	14
TLW0010F - Measure Trigger Pull Forces.....	15
TLW0010G - Measure Safe On/Off Forces.....	15
TLW0010H - Measure Bolt Lift and Bolt Closing Forces.....	16
TLW0010I - Measure Magazine Spring Force.....	17
TLW0010J - Measure Recoil Force.....	18
TLW0010K - Measure Lock Time.....	18
WEIGHTS OF MAJOR COMPONENTS - TLW0010L THROUGH TLW0010O:.....	20
TLW0010L - Overall Weight.....	20
TLW0010M - Weight of Stock Assembly.....	21
TLW0010N - Weight of Barrel Assembly.....	22
TLW0010O - Weight of Bolt Assembly.....	23
LENGTHS OF MAJOR COMPONENTS - TLW0010P THROUGH TLW0010R:.....	24
TLW0010P - Overall Length.....	24
TLW0010Q - Barrel Length.....	24
TLW0010R - Length of Pull.....	25
GUN CHARACTERISTICS - TLW0010S THROUGH TLW0010U:.....	26
TLW0010S - Balance Point.....	26
TLW0010T - Drop and Cast.....	27
TLW0010U - 50 lb. Trigger Pull Test.....	27
FIREARMS MEASUREMENTS - TLW0010V THROUGH TLW0010Z:.....	29
TLW0010V - Chamber cast.....	29
TLW0010W - Bore Diameter.....	29

J.R.Snedeker

Page 2 of 62

03/31/00

Rev - Non Confidential

Revision #2

ET07333

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010X - Groove Diameter:	30
TLW0010Y - Twist Rate (.30-06)	30
TLW0010Z - Magazine Capacity Test:	30
FUNCTION & ENDURANCE TESTING:	32
<i>FUNCTION AND ENDURANCE TESTING - TLW0010AA THROUGH TLW0010AE</i>	<i>32</i>
TLW0010AA - Basic Jack Function Test (to 200 Rounds):	32
TLW0010AB - Basic Shoulder Function Test:	34
TLW0010AC - Extended Function & Endurance:	35
TLW0010AD - Clean Rifles and Inspect:	38
TLW0010AE - Dry Cycle to 5000 Cycles:	38
ACCURACY TESTING:	40
<i>ACCURACY AND POI TESTING - TLW0010AF THROUGH TLW0010AG</i>	<i>40</i>
TLW0010AF - Point of Impact:	40
TLW0010AG - Group Size at 100 yards	41
ENVIRONMENTAL TESTING:	42
<i>TEMPERATURE & HUMIDITY - TLW0010AH THROUGH TLW0010AK</i>	<i>42</i>
TLW0010AH - Hot Function Test:	42
TLW0010AI - Cold Function Test:	42
TLW0010AJ - Thermal Cycle Test:	43
TLW0010AK - Heat & Humidity Function Test:	44
<i>DEBRIS TESTING - TLW0010AL THROUGH TLW0010AN</i>	<i>45</i>
TLW0010AL - Dynamic Sand & Dust Test:	45
TLW0010AM - Static Sand & Dust Test:	46
TLW0010AN - Field Debris Test:	49
<i>MISC. TESTS - TLW0010AO THROUGH TLW0010AP</i>	<i>50</i>
TLW0010AO - Rain Test:	50
TLW0010AP - Solvent Testing:	51
ABUSIVE TESTING	52
<i>IMPACT TESTING - TLW0010AQ THROUGH TLW0010AV</i>	<i>52</i>
TLW0010AQ - SAAMI Drop Test:	52
TLW0010AR - SAAMI Jar-Off Test:	54
TLW0010AS - SAAMI Rotation Test:	55
TLW0010AT - Extended SAAMI Jar-Off Test: (for Information only.)	56
TLW0010AU - Extended SAAMI Rotation Test: (for Information only.)	58

J.R.Snedeker

Page 3 of 62

03/31/00

Remington Confidential

Revision #2

ET07334

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

CONFIDENTIAL 83

Revision #2

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

M/710 Design Acceptance #1 Test Plan

Approvals

A meeting was held on 7 March 2000 to discuss the scheduled M/710 DAT #1 test. The purpose of this meeting was to define the test requirements for this Design Acceptance Test (DAT) scheduled to start in early March. During this meeting the test plan was reviewed step by step to determine what additional testing might be required to adequately test the product. This document lists the tests and procedures that have been agreed to by all meeting participants. Successful completion of these tests will qualify the Model 710 for Trial & Pilot evaluation.

The following people have reviewed this document and agree to this DAT #1 test protocol.

Dale Danner
Research & Technology

Scott Franz / Jim Snedeker
Test & Measurement Lab

Danny Diaz / Michael Keeney
Firearms Development

J.R. Snedeker

Page 5 of 62

03/31/00

Remington - Confidential

Revision #2

ET07336

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

**M/710 CENTERFIRE RIFLE
DESIGN ACCEPTANCE TEST PLAN - DAT #1**

Introduction:

This test is designed with the assumption that not all of the sample test guns will be available at the same start time. The initial test sample of 15 rifles will be delivered the second week in March (2000) and will be followed by an additional sample of 30-35 rifles delivered for test at a later time. Both sample sets are considered to be integral parts of the complete Design Acceptance Test Procedure.

The samples have been divided based on current estimates of sample delivery as follows. Rifles designated A1 to A15 are the first samples expected to be submitted for test on or about the 13th of March (2000) with a second group expected on about mid-May (2000) which will be designated as B1 to B30.

When successfully completing the proof test series, a 200 round per gun jack-function test is planned for the initial 15 rifle sample to quickly determine the probable malfunction rate and determine if the expenditure of further amounts of ammunition is justified by the performance of the product. Upon passing the jack-function test, the rifles will be subjected to 100 rounds per rifle test (twenty-five rounds each of four different bullet types). These rifles will be shot from the shoulder (standing position) in the long range to confirm that the rifles function as intended when shot in the same manner as expected to be used by the customer.

Various inspection points and safety reviews are scheduled into the test program.

Note that samples A1 through A15 will be shot using 3 aluminum stocks that will preclude some tests such as recoil and drop testing. The samples scheduled for delivery in mid-May will have the synthetic stocks designed for this model. Those tests requiring the use of the final design stock will be run at that time. The Intentional Abuse tests are scheduled during Phase I, (for rifles A1-A15) but will be tested without the stocks in place. Although not currently scheduled these tests may be repeated during Phase II if necessary.

J.R.Snedeker

Page 6 of 62

03/31/00

Revision #2

ET07337

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

When additional samples are submitted in mid-May, the test rifles will again, with a few exceptions, be subjected to the full range of standard rifle test procedures, comprised of Measurements, Accuracy, Function & Endurance testing, Environmental and Abusive testing.

CONFIDENTIAL

J.R.Snedeker

Page 7 of 62

03/31/00

Remington Confidential

Revision #2

ET07338

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Initial Tests, Measurements and Inspections:

HEADSPACE AND PROOF - TLW0010A THROUGH TLW0010C:

TLW0010A - Measure Headspace

All test samples will be measured for headspace before being tested in either the jack or shot from the shoulder. The chamber, bolt face & locking lugs on both the bolt and the receiver will be inspected for the presence of dirt or debris. If dirt or debris that could affect headspace measurement is present then these areas of the firearm will be cleaned before using the gauges.

Method:

- The graduated headspace gauges based on Remington chamber dimensions (Ref.: Remington Gauge Drawing # 41560 ...A, ...B, ...C, & ...D) will be used and the headspace measurements will be recorded to the nearest .001" increment as indicated by the gauge. The .30-06 Remington chamber drawing LB-153 will be used for chamber dimensions and LB-154 will be used for chamber drawings for the .270 caliber.
- The headspace measurements will be recorded to the nearest .001" increment as indicated by the gauge.
- If the measurement is taken at the start of the test then headspace should be less than Min. + .005".
- As the test progresses, headspace will be taken at each "Safety Inspection" scheduled in the plan and, in addition, at each "Clean & Inspect" activity scheduled by the plan.
- The readings for each firearm will be recorded on the "Daily Test Data Sheet" to be kept with each firearm in the accompanying data packet.
- For any firearms where the headspace is changing at each inspection point the firearm will be withdrawn from test and examined for the cause.
- In no case will any firearm in the test program be allowed to continue test if the headspace exceeds Min. + .009".

Data Required:

- Rifle serial number

J.R.Snedeker

Page 8 of 62

03/31/00

Revision #2

ET07339

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Headspace measurements for each sample

TLW0010B – Proof Test

All test sample firearms will be subjected to a standard .30-06 (or .270) Factory Proof Load, shot in the blow-up room using a lanyard. This procedure will be completed before the firearm can be used for any additional firing tests.

Before proof testing the firearm should be inspected for:

- Barrel Obstructions
- Bore and chamber are free of grease or oil and other debris.

For fully assembled firearms, one definitive proof cartridge should be fired in each firearm. Definitive proof ammunition is to be used in accordance with the "Handling of Ammunition" procedure defined in the SAAMI Technical Committee Manual, Volume III, Section II, Page 2410 as follows.

- "Cartridges to be tested should be placed in a vertical position with primer end down in a recessed holding block."
- "A cartridge should be lifted vertically from the block. It should be rotated slowly, end over end, in a vertical plane through 360° pausing momentarily when the powder is at the bullet end and again when the powder is at the primer end."
- "The cartridge is then rotated slowly, a minimum amount to enter chamber, keeping primer end in lowest possible position until inserted gently and carefully into the chamber."
- "The cartridge should be seated in the chamber as far as practicable with the fingers. The bolt or breech mechanism should be closed gently in order not to disturb the position of the powder in the cartridge case. The object of this method of handling cartridges is to position the propellant powder at the primer end of the cartridge case by permitting it to fall gently against the primer and while rotating the case."

J.R.Snedeker

Page 9 of 62

03/31/00

Revision #2

ET07340

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Note that these procedures for proof testing were developed to consistently position the propellant thereby providing greater consistency of proof pressures. Failure to follow this procedure during the definitive proof testing of each chamber of the firearm could result in pressure levels significantly below the minimum proof pressure specification as determined for the cartridge.

Any firearms components, such as bolts, bolt heads, receivers including chambers, etc. which were previously subjected to proof testing and, which subsequently, have any proof sensitive components changed, altered, or substituted, should be re-proofed.

Method:

- Record headspace before proof testing (*see previous procedure "TLW0010A - Measure Headspace."*)
- After firing the proof round, the firearm will be carefully examined to determine if any damage to the product has occurred due to exposure to the proof pressure. This inspection includes:
 - Visual inspection for damage,
 - damaged receiver or bolt, especially the locking lugs on the bolt or the receiver
 - bulged chamber or bore, split, cracked or otherwise damaged barrel,
 - broken stock,
 - any other part subjected to the proofing stress, which can be visually examined for damage.
 - Any "suspicious" areas should be submitted to magna-flux inspection before proceeding.
- ~~After~~ Magna-Flux all bolt heads after Proof.
- The fired proof cartridge should be examined to determine that no firearm fault has introduced cartridge failure, such as:
 - Expanded cartridge head.
 - Excessive roughness, rings, or bulging, which would affect extraction.
 - Beginning separation or material stretching in front of the case head indicating excessive headspace or excessive pressure as stated above.
 - Any cartridge case failure indicating a firearm fault.
- In addition, the spent proof round should be examined for the presence of unusual deformation, split case or split head, and for any evidence of a pierced primer. Any of these conditions may be indicative that high-pressure gases may have vented into the action where other damage to components may have occurred.

J.R.Snedeker

Page 10 of 62

03/31/00

Revision #2

ET07341

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Take note of any indication of significant gas leakage, if present, it may indicate that the firearm was not subjected to full proof pressures and the proof test would then be invalid and would require re-proofing.
- A firearm is only properly proofed when the cartridge has been fired without evidence of significant gas leakage.
- Save the spent proof case in a Zip-Lock plastic bag and label and place in the data packet for further reference. If any parts were broken or otherwise damaged, place these parts in the same bag as the proof case and label. Place a label on the firearm and withdraw the firearm from the test.
- Each sample firearms' headspace (*see following procedure "TLW0010C - Re-Measure Headspace after Proof"*) must remain in range from min. to min. $+0.007$ " after proofing, with no individual firearm's headspace to grow more than $.002$ " after firing one proof round. After successful proofing, the right lug on the bolt head will be marked in the center (i.e. center of top to bottom and center or front to rear) of the lug with a center punch to indicate that it has been proofed.
- After proof, if the firearm passes the inspection and headspace has been measured (*see next section of test plan*), stamp the firearm on the barrel with an authorized Remington proof stamp. Locate the proof mark on the right rear of the barrel in the specified location for the Remington proof stamp. **DO NOT STAMP** if the headspace exceeds Min $+0.007$.
- Because of the higher pressures involved in shooting proof cartridges, adequate precautions, both mechanical and procedural, should be taken to protect personnel performing the firearms proof testing. To this end, the firearm should be securely mounted, completely shielded from the operator and firing accomplished by a remote control method.

Data Required:

- Rifle serial number
- Record and note any headspace growth and the corresponding round level.
- Record significant gas leakage and/or firearm damage.
- Record any case damage or other ammunition related malfunctions.
- Record any damage to the firearm resulting from the proof test. Document with Photographs is necessary.

J.R.Snedeker

Page 11 of 62

03/31/00

REVISION 1

Revision #2

ET07342

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010C – Re-Measure Headspace after Proof

All test samples will be re-measured for headspace after proof and before being tested in either the jack or shot from the shoulder. The chamber, bolt face & locking block/locking notch will be inspected for the presence of dirt or debris. If dirt or debris that could affect headspace measurement is present then these areas of the firearm will be thoroughly cleaned before using the gauges.

Method:

- The graduated headspace gauges based on Remington chamber dimensions (Ref: Remington Gauge Drawing # 41560 ...A (min.), ...B (+.005), ...C (+.007), & ...D (+.009)) will again be used and the headspace measurements will be recorded to the nearest .001" increment as indicated by the gauge. The .30-06 Remington chamber drawing LB-153 will be used for chamber dimensions and LB-154 will be used for chamber drawings for the .270 caliber.
- The headspace measurement taken prior to the proof test should be less than min. + .005". If, after proof, the growth of the headspace is more than + .002" from the pre-proof condition, then stop and review the results with the test manager before continuing to the next phase of the test.
- In no case should the measurement for headspace after initial proof test be greater than min. +.007" for a new firearm.
- If at any time during the test program the headspace exceeds a maximum of Min. + .009" do not continue to fire the rifle, tag the gun with a label reading "Do Not Shoot This Firearm – Exceeds Maximum Allowable Headspace" and return the firearm to the Test Manager for disposition.

Data Required:

- Rifle serial number
- Record and note any headspace growth and round level.

J.R.Snedeker

Page 12 of 62

03/31/00

REVISION 1

Revision #2

ET07343

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

FORCES - TLW0010D THROUGH TLW0010K:

TLW0010D - Measure Firing Pin Indent:

The firing pin indent will be measured for each of the sample rifles using SAAMI qualified copper crushers. The average of three trials per sample rifle will be calculated. The Average of three indents must be equal to or greater than 0.017".

Method:

- Using copper crushers, "burnish" both ends of the crusher slug by gently rubbing both ends of the plate base of the dial indicator stand (use outside edge of the plate.)
- Place the copper crusher in a .30-06 / .270-crusher holder, place the crusher holder on the base of the dial indicator and zero the dial indicator with the point of the indicator in the approximate center of the crusher.
- Carefully, with the gun held so that the muzzle is pointed down toward the floor, gently insert the crusher holder into the chamber, being sure that the extractor clearance cut on the crusher is properly oriented relative to the extractor position.
- While maintaining a firm hold on the bolt handle, gently, and slowly ease the bolt forward to the full forward position and then rotate down being sure that the action locks fully.
- Holding the firearm in a horizontal and level position, and pointing the firearm in a safe direction, pull the trigger until the firing pin releases.
- Carefully open the action and remove the crusher holder, being careful not to drop the copper crusher.
- Leave the crusher in the holder and place under the dial indicator.
- Move the crusher holder so that the point of the dial indicator finds the deepest portion of the firing pin indent.
- Record the dial indicator reading to the nearest .001".
- Repeat procedure two more times and record the dial indicator readings using a new copper crusher for each trial.
- Each firearm sample should have three readings that will be averaged.
- Record all three readings for the data file.

J.R.Snedeker

Page 13 of 62

03/31/00

Revision #2

ET07344

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Data Required:

- Rifle serial number
- Each of the three trial indents
- The calculated average indent by rifle.

TLW0010E - Measure Sear/Trigger Engagement and Sear Lift:

The Sear/Trigger Engagement will be measured. The amount of engagement must be measured between .020" and .025" measured with the bolt in the fully closed and locked position.

Method for measuring Sear/Trigger Engagement:

- The 30" Optical comparator will be used to measure the engagement at 50X magnification.
- With the barreled action held firmly in position, the barreled action will be aligned such that the action is held perpendicular to the lens in both the horizontal and vertical planes.
- With action closed and locked, the safety in the "fire" position, measure the amount of overlap between the sear and the trigger.

Method for measuring Sear Lift:

- Remove the bolt from the action.
- Place the Safety in the "Off-Safe" (i.e. "Fire") position.
- With the action held firmly in a horizontal position pre-load the sear in the downward position using a small screwdriver and with a dial indicator zeroed on the top of the sear, gently rotate the Safety to the "On-Safe" position.
- Record the amount of vertical movement of the sear.
- Minimum sear lift is 0.006" and maximum sear lift is 0.018"

Data Required:

- Rifle Serial number
- Record Sear/Trigger Engagement
- Record Sear Lift

J.R.Snedeker

Page 14 of 62

03/31/00

Remington Confidential

Revision #2

ET07345

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010F - Measure Trigger Pull Forces:

Trigger pull (force and displacement required to manually operate the trigger)

Method:

- Trigger pull is to be performed to the SAAMI standard; horizontal pull at the center of the finger radius of the trigger using the Test Lab apparatus designed for taking this measurement.
- Use the 1-10 lb. Chatillion Force digital force gauge.
- Force is measured parallel to the bore with the stock assembled to the action.
- Three pulls are to be taken on each sample rifle and the results averaged.
- The average force for the three trials must be between 3.5 lb. and 5.0 lb.

Data Required:

- Rifle Serial number
- All three data points for each trial rifle
- The average of the three measurements for each sample rifle.

TLW0010G - Measure Safe On/Off Forces:

Using the Chatillion Digital force gauge and the wooden holding fixture used to take trigger pull readings, push the Safe to the "Safe Off" position on each test sample. Complete three trials. Record all three readings for each firearm. Repeat the test, this time pushing the Safe to the "Safe On" position on each trial. Record all three readings. Average each of the three sets of readings in each direction for each test sample. These measurements are for information only. A minimum of 1 lb. force in either direction will be assumed as the reference criteria.

Method:

- Use trigger pull apparatus to hold the rifle for this test.
- Use the Chatillion Digital Force gauge (0-10 lb. range) with the disc point or the "v" shaped point. Use the same tip on all subsequent trials.
- Make three trials in each direction for each sample.

J.R.Snedeker

Page 15 of 62

03/31/00

REMOVED FOR CONFIDENTIALITY

Revision #2

ET07346

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Average the results of each of the three trials.
- For Phase II rifles, the ISS system will be checked.

Data Required:

- Rifle serial number
- Each of the three readings for each direction on each sample
- The average of each of the three sets of readings
- The results of the ISS system check.

TLW0010H - Measure Bolt Lift and Bolt Closing Forces:

The force required opening the bolt and closing the bolt will be measured for each sample. Both of these forces will be taken with the chamber empty and then repeated, this time with a new dummy round in the chamber. There is not a specification for these forces and the readings will be taken for information only.

Method:

- After locating the rifle in the trigger pull fixture and securely locking in place, (it may be necessary to clamp the fixture to the bench if not already securely fixed in place), locate the hook of the force gauge at the point on the bolt handle just behind the ball.
- With the chamber empty and using the Chatillon gauge, pull the gauge straight up and perpendicular to the bore, measure the force required to open the bolt.
- Lock the firearm in a horizontal position, using the trigger pull holding fixture, (i.e. shooting position) before taking the measurements.
- Take three readings for each gun in the sample.
- Record all readings.
- Repeat the procedure only this time push the bolt closed.
- Note that it may be necessary to start the bolt closed by hand so the firing pin head is depressed sufficiently out of the notch and can start up the cam surface of the bolt as the firing pin is cocked.
- Repeat the above procedure this time with a new, unused dummy round in the chamber.

J.R.Snedeker

Page 16 of 62

03/31/00

Remington - Confidential

Revision #2

ET07347

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WESTRING ROAD
ELIZABETHTOWN, KY 42701

Data Required:

- Rifle serial number
- Each of the three readings taken for each of the 4 states for each test sample
- The average of each set of three measurements per state

TLW0010I - Measure Magazine Spring Force:

The force produced by the compression of the Magazine Spring in the box with the follower attached will be measured. These measurements will be taken for information only. There is no specification currently defined for this characteristic.

Method:

- Use the Chatillion TCD200 Spring Testing Machine with the Chatillion Digital Force Gauge (0-10 lb. range). Use the disc probe (1/2" dia.) on the gauge.
- Place the magazine box, bottom side down, on the staging table.
- Zero force gauge with no load applied.
- Lower the gauge until it just touches the magazine follower, approximately in the middle location both side to side and front to rear.
- Zero force gauge again if necessary.
- Lower the gauge 0.200" and take the spring force measurements.
- Lower the gauge another 1.0".
- Take the force measurement at this depressed location of the spring.
- Repeat procedure two additional trials for each box.
- Average the 3 trials for each box and at each measurement location.

Data Required:

- Force Measurements taken on each trial per box at each of the measurement locations.
- The Average Force measurement per box.
- The serial number of the Chatillion Digital Force Gauge used for the procedure.

J.R.Snedeker

Page 17 of 62

03/31/00

Remington Confidential

Revision #2

ET07348

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010J - Measure Recoil Force:

Using the Remington designed recoil force device, measure the recoil forces for both the .30-06 and .270 caliber rifles. This test will only be done during Phase II with the synthetic stocks assembled to the actions. The measurements will be taken for information only.

Method:

- Assemble device to stock.
- Shoot the test in "blow-up" range using the jack. Fire the rifle remotely. (As an alternative, the rifle may be shot from the shoulder, with prior review of the safety status of the firearms.)
- Use the round with the heaviest available factory bullet.
- Shoot ten rounds per sample rifle.
- Average the ten rounds for each sample.

Data Required:

- Rifle serial number
- The peak force and area under the curve will be calculated for each shot for which data is captured.
- A plot of each shot, 4 signals captured per shot (3 for force and 1 for acceleration.)
- The average for peak force and areas under the curve of the ten trials per rifle.

TLW0010K - Measure Lock Time:

Using the Remington method of measuring Lock Time, measure the lock time on the sample rifles provided. Do three trials on each sample rifle. Average the three trials. This data is for information only. The expectation is that lock time will be in the 3-msec. range. This test is scheduled for Phase I testing but may have to be postponed until Phase II if the metal stocks create a measurement problem.

Method:

- Standard Remington Lock Time Measurement procedure. (Sear Safety Cam release to 1st firing pin contact with the primer.)

J.R.Snedeker

Page 18 of 62

03/31/00

Remington Confidential

Revision #2

ET07349

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Measure three lock times per sample rifle

Data Required:

- Rifle serial number
- Each lock time trial
- Average lock time per rifle
- Settings used on the equipment.

CONFIDENTIAL

J.R.Snedeker

Page 19 of 62

03/31/00

Remington Confidential

Revision #2

ET07350

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

WEIGHTS OF MAJOR COMPONENTS - TLW0010L THROUGH TLW00100:

Note: The Weight measurements are scheduled for Phase II when the synthetic stocks are available for test.

TLW0010L - Overall Weight:

The test samples will be weighed on the Mettler Toledo digital balance (PB8000) located in the Metrology Lab. The rifles will be weighed once each with the chamber and magazine empty. The rifle will have only the open sights attached, no scope or other accessories attached.

Method:

- Clean the platen of the digital balance, if necessary.
- If the balance is not already on and has been turned on at least 30 minutes for warm-up, turn the balance on and wait 30 minutes for the balance circuitry to stabilize.
- Run the balance calibration routine if necessary.
- Make sure the units are set to "lb."
- With the chamber empty and the magazine box empty of rounds, carefully place the rifle on its left side with the rifle's approximate front to rear balance point directly over the center of the balance platen.
- When the scale settles down, record the weight in lb. to the nearest 0.1 lb. (Note that the scale has three decimal points displayed.)

Data Required:

- Rifle serial number.
- Weight to the nearest 0.1-lb.
- Serial number of the Mettler PB8000 balance (it should be SN 2114475246)

J.R.Snedeker

Page 20 of 62

03/31/00

Remington Confidential

Revision #2

ET07351

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010M - Weight of Stock Assembly:

The stock, disassembled from the barreled action, will be weighed. (Synthetic stock only.) The test samples will be weighed on the Mettler Toledo digital balance (PB8000) located in the Metrology Lab. The rifle's stocks will be weighed once each.

Method:

- Clean the platen of the digital balance, if necessary.
- If the balance is not already on and has been turned on at least 30 minutes for warm-up, turn the balance on and wait 30 minutes for the balance circuitry to stabilize.
- Run the balance calibration routine if necessary.
- Make sure the units are set to "lb."
- Label the stock as to which barreled action it came from.
- Carefully place the stock on its left side with the stock's approximate front to rear balance point directly over the center of the balance platen.
- When the scale settles down, record the weight in lb. to the nearest 0.1 lb. (Note that the scale has three decimal points displayed.)

Data Required:

- Rifle serial number
- Weight to the nearest 0.1-lb.
- Serial number of the Mettler PB8000 balance (it should be SN 2114475246)

J.R.Snedeker

Page 21 of 62

03/31/00

Remington Confidential

Revision #2

ET07352

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010N - Weight of Barrel Assembly:

The barreled action, disassembled from the stock, will be weighed. Remove the bolt assembly from the barreled action. The test samples will be weighed on the Mettler Toledo digital balance (PB8000) located in the Metrology Lab. The rifle's barreled actions will be weighed once each.

Method:

- Tag the bolt so that it is labeled with the last four digits of its rifle's serial number. This bolt assembly must be returned to its original rifle or the headspace may change.
- Clean the platen of the digital balance, if necessary.
- If the balance is not already on and has been turned on at least 30 minutes for warm-up, turn the balance on and wait 30 minutes for the balance circuitry to stabilize.
- Run the balance calibration routine if necessary.
- Make sure the units are set to "lb."
- Carefully place the barreled action on its left side with the barreled action's approximate front to rear balance point directly over the center of the balance platen.
- When the scale settles down, record the weight in lb. to the nearest 0.1 lb. (Note that the scale has three decimal points displayed.)
- Reassemble the stock on its corresponding barreled action.

Data Required:

- Rifle serial number
- Weight to the nearest 0.1-lb.
- Serial number of the Mettler PB8000 balance (it should be SN 2114475246)

J.R.Snedeker

Page 22 of 62

03/31/00

Remington Confidential

Revision #2

ET07353

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW00100 - Weight of Bolt Assembly:

The bolt assembly, disassembled from the rifle, will be weighed. The test samples will be weighed on the Mettler Toledo digital balance (PB8000) located in the Metrology Lab. The rifle's bolt assembly will be weighed once each.

Method:

- Check to be sure that the bolt is correctly tagged with the last four digits of its rifle's serial number. This bolt assembly must be returned to its original rifle or the headspace may change.
- Clean the platen of the digital balance, if necessary.
- If the balance is not already on and has been turned on at least 30 minutes for warm-up, turn the balance on and wait 30 minutes for the balance circuitry to stabilize.
- Run the balance calibration routine if necessary.
- Make sure the units are set to "lb".
- Carefully place the bolt assembly with the bolt assembly's approximate front to rear balance point directly over the center of the balance platen.
- When the scale settles down, record the weight in lb. to the nearest 0.1 lb. (Note that the scale has three decimal points displayed.)
- Re-assemble the bolt on its corresponding barreled action.

Data Required:

- Rifle serial number
- Weight to the nearest 0.1-lb.
- Serial number of the Mettler PB8000 balance (it should be SN 2114475246)

J.R.Snedeker

Page 23 of 62

03/31/00

Remington - Confidential

Revision #2

ET07354

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

LENGTHS OF MAJOR COMPONENTS - TLW0010P THROUGH TLW0010R:

TLW0010P - Overall Length:

Phase II measurement of Overall Length of the firearm. For information only.

Method:

- Set butt of gun on the floor near a wall
- Bring the top of the barrel to the wall so that the top of the barrel lies even with the wall surface
- Measure the distance from the floor to the end of the muzzle using a tape measure.

Data required:

- Rifle Serial number
- Measurements for each sample rifle.

TLW0010Q - Barrel Length:

Measure the length of the barrel. For the .30-06 and .270 caliber, the barrel length should be $22" \pm .125"$ measured from the bolt face to the end of the muzzle.

Method:

- Check firearm for live ammunition
- Close bolt over and empty chamber
- With the butt of the rifle on the floor and the muzzle pointing up, carefully and gently, so as to not scratch the bore or nick the rifling, insert a brass rod (not steel) into the muzzle of the rifle until it stops on the bolt face. Move the brass rod around to insure that you are on the bolt face and not on the edge of the ejector or extractor.
- Carefully mark the brass rod where it is even with the edge of the muzzle
- Remove the rod and measure the length.

J.R.Snedeker

Page 24 of 62

03/31/00

Remington - Confidential

Revision #2

ET07355

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Data Required:

- Rifle serial number
- Measurement of barrel lengths in inches.

TLW0010R - Length of Pull:

Length of Pull – the distance from the center of the butt plate (from center of top (i.e. heel) to center of bottom (i.e. toe)), to the inside curve of the trigger. Measurements are taken for information only.

Method:

- With muzzle of rifle pointed down and barrel clamped securely in holding device
- Located the center of the distance, top to bottom of the butt pad and mark pad or butt plate
- Measure to the inside curve of the trigger (at the front)

Data Required:

- Rifle serial number
- Length of Pull measurements

J.R.Snedeker

Page 25 of 62

03/31/00

Remington Confidential

Revision #2

ET07356

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

GUN CHARACTERISTICS - TLW0010S THROUGH TLW0010U:

TLW0010S - Balance Point:

Balance Point - Phase II measurement. Establish the balance point for this firearm. (This measurement will also be used later for the SAAMI drop test.)

Method:

- Using a right angle block from the metrology lab, invert the block to provide a "sharp edge".
- Close the action over an empty chamber and with the magazine empty.
- Using two hands, carefully place the firearm in a horizontal orientation, over the edge of the angle block with the bottom of the firearm in the down position.
- Again, using two hands, one on each side of the block edge about one foot from the block edge front to rear, carefully place the firearm on the edge and attempt to locate the balance point.
- With the assistance of another individual, place a light pencil mark at the likely balance point. After removing the firearm from the edge, measure the distance to the breech face with the bolt in the closed position. (The position of the breech face was determined when the barrel length was measured. This location, that is, the breech face can be established by measuring the specific distance from the muzzle to outside of the receiver and marked accordingly. The distance from the balance point to this breech face mark is the location of the balance point.)
- Repeat this procedure for the following condition:
 - Using .30-06 dummy shells, place one in the chamber and four in the magazine, close the action and measure the distance to the bolt face.

Data Required:

- Record rifle serial number
- Record balance point with firearm empty
- Record balance point with firearm "loaded"

J.R.Snedeker

Page 26 of 62

03/31/00

Remington Arms Company

Revision #2

ET07357

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010T - Drop and Cast:

Drop at the comb – the distance from an imaginary line drawn along the top edge of the receiver to the foremost position of the comb.

Drop at the Heel - the distance from an imaginary line drawn along the top edge of the receiver to the point on the heel of the stock.

Both of these dimensions are for information only.

Cast off (or cast on) – Not required for rifle stocks.

Method: (for drop at Comb)

- Align the top of the receiver along back edge of the Drop Board
- Measure the distance from the Drop Board to the front-most position of the Comb
- Record the distance to the nearest 1/8"

Method: (for drop at Heel)

- Using the same procedure as mentioned above, measure the distance from the closest point on the top of the heel (just ahead of the butt-pad or butt-plate backer at the edge of the stock proper) to the back of the Drop Board. Record distance to nearest 1/8"

Data Required:

- Record rifle serial number
- Record drop at comb
- Record drop at heel

TLW0010U – 50 lb. Trigger Pull Test

This test is conducted to determine if the safety mechanism will release the trigger mechanism and cause the firearm to discharge if the trigger is pulled intentionally by the shooter with the safety on the "On-Safe" position. In addition, sufficient force is applied to the trigger with the safe in the "On-Safe" position to assure

J.R.Snedeker

Page 27 of 62

03/31/00

Remington Confidential

Revision #2

ET07358

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

that the trigger dimensions will not change thereby affecting trigger/sear engagement. Prior to start of test verify that trigger pull, engagement and over-travel are within recommended specifications on the sample rifles.

- Inspect and verify the rifle is not loaded and the safe is in the "On-Safe" position.
- Locate the firearm in a vertical position with the muzzle pointed up.
- Using the set of plug gauges determine the amount of minimum clearance between the rear of the trigger and the inside rear of the trigger guard. This dimension will be used as a reference to see if the trigger has been deformed by the loading in the next steps.
- Carefully load a primed case into the chamber and close the bolt.
- With the safe in the "On-Safe" position, using the NRA trigger pull rod, load the trigger with a 30lb. weight. **BE EXTREMELY CAUTIOUS TO STAY CLEAR OF THE MUZZLE IN CASE THE FIREARM DISCHARGES THE PRIMED CASE.**
- Remove the load from the trigger.
- Move the Safety to the "Fire" position, the rifle must not discharge.
- Return the Safety to the "On-Safe" position.
- Carefully remove the rifle from the holding device and with the muzzle pointed in a safe direction, pull the trigger, the rifle must discharge. Extract the shell case.
- Using the plug gauges measure the minimum clearance between the rear of the trigger and the inside rear of the trigger guard.
- Measure the trigger pull, engagement and over-travel to insure that they have not changed from the beginning of the test.

Data required:

- Rifle serial number
- Measurements of Trigger pull, engagement, over-travel and trigger/trigger guard clearance before and after loading.
- Note that the rifle "fired" or did not fire when the safety was pushed to the "Fire" position.
- Note that the rifle did "fire" when the trigger was pulled.

J.R.Snedeker

Page 28 of 62

03/31/00

Revision #2

ET07359

- 247 -

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

FIREARMS MEASUREMENTS - TLW0010V THROUGH TLW0010Z:

TLW0010V - Chamber cast:

Use the .30-06-chamber drawing LB-153 for reference.

Method:

- Make chamber cast using standard procedure
- Use the 30" optical comparator
- Measure the following dimensions:
 - .4708/.4728
 - .4425/.4440
 - 34° 30" Angle
 - .3404/.3424
 - .3095/.3105

Data Required:

- Rifle serial numbers
- Record dimensions requested above.

TLW0010W - Bore Diameter:

Measure Bore Diameter using standard procedures.

Method:

- Measure .30-06 caliber
- Dimension equals .300/.301

Data Required:

- Rifle serial numbers

J.R.Snedeker

Page 29 of 62

03/31/00

Remington Confidential

Revision #2

ET07360

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Measurements of each bore by serial number

TLW0010X - Groove Diameter:

Measure Groove Diameter using standard procedures.

Method:

- Measure .30-06 caliber
- Dimension equals .308/.309

Data Required:

- Rifle serial numbers
- Measurements of each bore by serial number

TLW0010Y - Twist Rate (.30-06)

Measure Twist Rate using standard procedures.

Method:

- Measure .30-06 caliber
- 1 turn in 10" - 25" RH

Data Required:

- Rifle serial numbers
- Measurements of each bore by serial number

TLW0010Z - Magazine Capacity Test:

Rifles with the magazine fully loaded must be able to be inserted into firearm with the bolt closed and in the locked position. Model 710 must be able to accept 4 rounds in the magazine and load into a closed bolt.

Method:

- Check rifle for live ammunition

J.R.Snedeker

Page 30 of 62

03/31/00

Remington Confidential

Revision #2

ET07361

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- With muzzle pointed in a safe direction, close the bolt and lock over an empty chamber
- Load 4 dummy rounds into the magazine
- Insert magazine into the rifle, it must lock securely in place
- Cycle the 4 dummy rounds through the chamber and eject each round
- Remove the magazine box and repeat test two additional times per sample rifle using a different magazine box each trial.

Data Required:

- Rifle serial number
- Record any failures to load and cycle properly by box and rifle

J.R.Snedeker

Page 31 of 62

03/31/00

Remington Confidential

Revision #2

ET07362

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

FUNCTION & ENDURANCE TESTING:

FUNCTION AND ENDURANCE TESTING - TLW0010AA THROUGH TLW0010AE

TLW0010AA - Basic Jack Function Test (to 200 Rounds):

To get an early picture of the product's functional capability, a 200 round per rifle jack function test will be conducted. Five bullet types will be used, 40 round of each in each rifle to evaluate the potential for feeding problems. The test will be conducted in the test jacks with the "belly-protectors" in place and fully closed for each shot. All malfunctions and any unusual behavior will be noted on the data forms. The overall average of all sample rifles should be at or below 2-% malfunction rate. Up to two rifles from the sample of 15 are permitted to be removed from the averaging process if they have excessive malfunction rates relative to the remaining group of 13 samples. These rifles will be investigated by engineering to determine the probable source of the problem and engineering will provide written documentation for possible inclusion in the DAT report. No major mechanical failures are allowed in the test sample. Major mechanical failures are defined as those failures that cannot easily be repaired with simple tools and/or readily available replacement parts. At the conclusion of this test, the firearms will be carefully examined for signs of excessive wear, especially with respect to the plastic components.

Method:

- Check each rifle for the presence of the proof stamp(s) - do not shoot unless the stamp(s) are present.
- Check each rifle for headspace
- Draw ammunition from stores - See test manager for ammo types to be used for this test.
- Each tester to have five rifles for test at any given time.
- The muzzle of each rifle will be inserted into the shooting port and the rifle placed securely in the test jack before the rifle is loaded.
- Load the five rounds into the rifle, one in the chamber and four in the magazine, do not shoot single shot by hand-feeding single rounds into the chamber.

J.R.Snedeker

Page 32 of 62

03/31/00

Revision #2

ET07363

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Push the safe to the "fire" position, be sure that the barrel is far enough within the port hole so that the muzzle will stay in the port when the rifle recoils. If there is any question, re-adjust the jack into a better position.
- With the lid on the belly protector closed, fire the first round in the chamber, listen for any off-sounds, and be alert for any other unusual behavior.
- Open the bolt; eject the spent round, note any extraction or ejection problems.
- Close the bolt to load the first round from the magazine into the chamber, note any feeding or stemming problems.
- Continue to fire the remaining rounds in the magazine until the last round is fired.
- Push the Safety to "On Safe" position, the safety will be pushed to the fire position at the start of every five round trial and will be pushed to the On Safe position at the end of every five round trial. Repetitive action of the safety lever on the trigger assembly side-plate needs to be determined.
- After firing twenty rounds (1 box of ammo) the rifle will be checked carefully for the presence of any live ammunition and if empty will be removed from the test rack and placed in the cooling rack. The safety will be in the "On Safe" position and the bolt will be unlocked and fully open at all times. Compressed air may be used, if necessary to cool the inside of the chamber area if the rifle is excessively hot from firing.
- All malfunctions will be recorded on the data sheets.

Data Required:

- Rifle serial number
- Tester's name
- Date of test firing
- The TLW#
- The ammunition used for the test with the ammo lot code number of the rounds actually used.
- Any malfunctions noted or other unusual items of note.

J.R.Snedeker

Page 33 of 62

03/31/00

Revision #2

ET07364

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WESTRING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AB - Basic Shoulder Function Test:

To get an early picture of the product's functional capability from the perspective of the customer, a 100 round per rifle shoulder function test will be conducted to evaluate the potential for feeding problems. These malfunctions may be different from those noted in the jack test due to shooter reactions to recoil potentially affecting round position in the magazine box. The test will be conducted in the long range shooting from a standing position. Twenty-five (25) rounds each of four (4) different bullet types will be shot in each sample rifle.

All malfunctions and any unusual behavior will be noted on the data forms. The overall average of all sample rifles should be at or below the 2% malfunction rate. All rifles must pass the 2% criteria due to the small number of rounds being fired. No major mechanical failures are allowed in the test sample. Major mechanical failures are defined as those failures that cannot easily be repaired with simple tools and/or readily available replacement parts. At the conclusion of this test the firearms will be carefully examined for signs of excessive wear, especially with respect to the plastic components.

Method:

- Check each rifle for the presence of the proof stamp(s) – do not shoot unless the stamp(s) are present.
- Check each rifle for headspace
- Draw ammunition from stores – See test manager for ammo types to be used for this test.
- Perform all range preparations required for shooting in the long range. Make sure the range ventilation is turned on.
- Wear safety glasses with side shields and double hearing protection.
- When ready to fire, the tester should stand in the doorway of the long range and when firing should be careful to keep the bullets in the center of the range to prevent damage to shields, lights, etc.
- Load the five rounds into the rifle, one in the chamber and four in the magazine, do not shoot single shot by hand-feeding single rounds into the chamber.
- Push the safe to the "fire" position,
- Fire the first round in the chamber, listen for any off-sounds, and be alert for any other unusual behavior.

J.R.Snedeker

Page 34 of 62

03/31/00

Revision #2

ET07365

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Open the bolt; eject the spent round, note any extraction or ejection problems.
- Close the bolt to load the first round from the magazine into the chamber, note any feeding or stemming problems.
- Continue to fire the remaining rounds in the magazine until the last round is fired.
- Push the Safety to "On Safe" position, the safety will be pushed to the fire position at the start of every five round trial and will be pushed to the On Safe position at the end of every five round trial. The effect of the action of the safety lever on the trigger assembly side-plate needs to be determined.
- After firing ten rounds the rifle will be checked carefully for the presence of any live ammunition and if empty will be placed in the cooling rack. The safety will be in the "On Safe" position and the bolt will be unlocked and fully open at all times. Compressed air may be used, if necessary to cool the inside of the chamber area if the rifle is excessively hot from firing.
- All malfunctions will be recorded on the data sheets.

Data Required:

- Rifle serial number
- Tester's name
- Date of test firing
- The PLW#
- The ammunition used for the test with the ammo code number of the rounds actually used.
- Any malfunctions noted or other unusual items of note.

TLW0010AC - Extended Function & Endurance:

This Endurance Test will be shot to accomplish two purposes. The first purpose is to determine an estimate of the product's expected malfunction rate over an extended period of shooting. The second is to determine both the estimated life of individual components as well as the expected life (in rounds) of the product before system failure occurs. For purposes of definition, a component failure will be one that prevents (or could prevent) the firearm from functioning as intended. These are failures that can be fixed relatively easily by the simple replacement of a part such as could be done by the gun owner using only simple household tools.

J.R.Snedeker

Page 35 of 62

03/31/00

Not for Distribution

Revision #2

ET07366

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

System failures are defined as failures of a major nature, the extent of which would require specialized tooling or methods to repair not normally available to the average gun owner. Such a repair would be most likely made by a qualified gunsmith or by return to the factory.

This Endurance Test will be shot in the test jacks and the testers will use gloves for protection. The covers on the "belly-protectors" will be down and in-place for each test shot. Careful monitoring of each test gun is essential to evaluate the malfunction rate for each firearm.

The standard Remington test jacks will be used for all jack-related testing.

Each rifle will be shot, using a variety of Centerfire ammunition comprised of light, medium and heavy bullets. In addition, ammunition from the three major manufacturers (Remington, Winchester and Federal) of Centerfire ammunition shall be included in the mix.

Each rifle will be shot no more than 20 rounds before being put aside for cooling. Compressed air applied to the inside of the chamber will be an acceptable method to assist in the cool-down process.

The S.A.A.M.I. recommendation for the minimum acceptable malfunction rate for a bolt action rifle is a malfunction rate of < 2%. In this case, if the overall malfunction rate average for the test samples is > 2%, the DAT test will be stopped and the guns returned to Design for modification and improvement before being re-submitted for DAT. If the overall average malfunction rate is < 2% but one of the firearms is significantly greater than 2% malfunction rate, the test may continue with the other nine test samples while Design attempts to fix the problem with malfunctioning gun. After repair, this gun will again be required to pass the 200 round jack function test at < 2% malfunction rate. If the gun passes these criteria it will then be re-introduced into the Endurance test. It is important that total endurance rounds on the gun include any rounds that are put through the gun for re-test purposes.

The test will be performed according to Remington's standard endurance test procedures for centerfire rifle. Pyramid for this test will be ten rifles to 1,000 rounds, six rifles to 2,000 rounds, three rifles to 5,000 rounds and one rifle to 10,000 rounds.

Record all instances of malfunctions and failures, and replace parts when they become unserviceable noting the round level when they were replaced.

After every 100 rounds one live round will be extracted and ejected from the chamber to check on live round ejection. The ejected round will then be re-inserted into the chamber and fired to help keep the endurance round count accurate.

J.R.Snedeker

Page 36 of 62

03/31/00

Revision #2

ET07367

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Method:

- Disassemble, thoroughly clean, lubricate per the design team's instructions, and reassemble. Record headspace for each.
- Fire each test firearm in accordance with the firing procedure (number of rounds, firing cycle) specified by engineering and the test plan.
- Ammunition will be used that comprises at least five types of bullets, change ammunition type every 100 rounds.
- Before commencing design acceptance testing, calibrate, adjust, or re-build the shooting jacks, if necessary.
- Allow the firearm to completely recover in the shooting jack between each shot and do not lean or "stiff arm" the firearm while shooting the gun.
- All ammunition is to be functioned through the magazine, no "single shot" hand feeding permitted.
- Allow the rifle to cool between cycles. One cycle is 20 rounds fired. The use of forced air to accelerate cooling of the barrels between firing trials is permitted. The air should be directed from the chamber toward the muzzle to prevent it from washing the lubricant from the firearm's action.
- Cycle the safety from Fire to Safe every 5 rounds, from Safe to Fire at the start of the five round cycle and from Fire to Safe at the end of the 5 round cycle.
- After every 1000 rounds, disassemble, inspect, clean and lubricate the entire mechanism and take all required measurements.
- At the initial 1000, initial 5000 and at the 10,000 round level, Magna-Flux the bolt heads.
- The Standard Remington Jacks (using the heavy configuration) are to be used for this test.

Data Required:

- Rifle serial number
- Tester's name
- The Test Jack Identification
- TLW#
- Date of actual testing
- Headspace every 1000 round interval.
- Malfunctions per ammo type, breakage, and replacement parts used.

J.R.Snedeker

Page 37 of 62

03/31/00

Remington Arms Company Inc.

Revision #2

ET07368

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Any failure that requires the gun to be removed from testing completely.
- Notify management of any unusual events or malfunctions immediately.
- Any firing of the firearm without the trigger being pulled.
- Record ammunition lot code information as it is used throughout the test.
- Bullet type used for each 100 rounds of the test.
- The results and photographs, if any, of the Magna-Flux testing.

TLW0010AD - Clean Rifles and Inspect:

After each 1000 rounds of endurance, unless other wise specified, each rifle will be disassembled, cleaned and thoroughly inspected.

A list of inspection points will be provided in the gun packet for check-off and sign-off by the inspector. The inspector will be looking for any signs of unusual wear, especially on critical components and surfaces as well as for anything such as cracks or deformed material that might present a safety concern. Photographs will be taken to document unusual wear, damage or other notable characteristics.

TLW0010AE - Dry Cycle to 5000 Cycles:

The bolt assembly will be dry cycled to determine reliability due to mechanical wear as well as verify the long term performance and reliability of the bolt and receiver assembly. The M/700 dry cycle fixture will be used to perform this test by mounting the M/710 bolt / firing pin / firecontrol assembly and cycling to a 5000 cycle level. Bolt galling and other M/710 common part failures will be noted relative to this test.

Of particular interest in this test will be the effects of wear on the plastic components in the receiver and firecontrol.

For comparison purposes a new Model 700 fire control will be run in parallel through the dry cycle machine. Headspace will be checked on both actions at each 1000 round level to determine if the lugs are wearing excessively. Photographs will be taken at the start of the dry cycle test of the bolt lugs, cam surfaces

J.R.Snedeker

Page 38 of 62

03/31/00

Revision #2

ET07369

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

and other critical wear areas and repeated at each 1000 cycle level. Photographs of each critical area will be taken at each inspection level, after cleaning. Each model will be lubricated after cleaning and inspection according to the instructions that will be found in its owner's manual.

CONFIDENTIAL 83

J.R.Snedeker

Page 39 of 62

03/31/00

Remington Confidential

Revision #2

ET07370

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

ACCURACY TESTING:

ACCURACY AND POI TESTING - TLW0010AF THROUGH TLW0010AG

TLW0010AF - Point of Impact:

Note: This will be a Phase II test only. The barrels for Phase I will not have been angularity straightened.

The point of impact test involves the verification of the firearms sighting system adjustment and the potential to hit the point of aim. The open sights must have sufficient adjustment in either direction when the rifle is sighted in at 100 yards. Random variation and/or extreme difference in shot to shot point of impact (as well as group size) typically indicate improper barrel processing and is used as a final inspection flag in production. This test will be shot from the bench with open sights. Shoot five, 5-shot groups from each test rifle. Use the same code of ammunition for all point of impact test shots.

Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Pick the point of aim on the target
- Adjust point of aim to the bulls-eye at 100 yards.
- Slide must be adjusted to between the second line from the rear to third line from the front.
- The aperture must have the width of the screw retaining shoulder visible to either side.
- Shoot five "warmer" shots
- Shot five, 5-shot groups

Data Required:

- Measure the center of the impact groups to the point of aim in terms of "x" and "y" positions.
- Record takedown screw torque
- Record position of slide when shot
- Record ammunition lot number used during the test
- Record and label any fail-to-fire ammunition

J.R.Snedeker

Page 40 of 62

03/31/00

Remington - Confidential

Revision #2

ET07371

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AG - Group Size at 100 yards

One hundred-yard accuracy testing will be completed utilizing standard factory ammunition. The test will consist of five, 5-shot groups. Guns will be cooled after every other group. Each firearm will be cleaned and fired with five fouling shots prior to beginning the accuracy work-up. Group sizes will be measured from actual targets and recorded. The same code of ammunition and same type of ammunition will be used for all group size test shots. Average group sizes must be $\leq 3"$ at 100 yards.

Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Fire five, 5-shot groups at 100 yards, using a 36 power scope for each ammunition type selected. Prior to beginning of the test, clean the bore and shoot 5 "fouling" shots to seat in the rifle.
- Cycle the safety from fire to safe every 5 rounds.
- Accuracy should be shot from a recoiling rest. Shoulder shooting is acceptable but not the preferred way.

Data Required:

• Measure group sizes center to center

- Record takedown screw torque
- Record make and identifier of scope
- Record ammunition type used.
- Record ammunition lot numbers used during the test
- Record and label any fail-to-fire ammunition.
- Record any malfunctions that occur during the test.

J.R.Snedeker

Page 41 of 62

03/31/00

Remington Confidential

Revision #2

ET07372

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

ENVIRONMENTAL TESTING:

TEMPERATURE & HUMIDITY - TLW0010AH THROUGH TLW0010AK

TLW0010AH - Hot Function Test:

This test evaluates the effect of extreme high temperatures on the functioning performance of firearms.

Method:

- Condition test firearm and 100 rounds of ammunition of each caliber in a climatic chamber for at least 6 hours at a temperature of 120 degrees F. (or as close to 120 degrees F. as the equipment can be maintained.)
- Test each firearm within the chamber as follows:
 - Fire 20 rounds of ammunition. Wait 2 hours and repeat until all 100 rounds have been fired.
 - Do not perform maintenance during the 100 round cycle.
 - Cycle the safety from fire to safe every 5 rounds.
 - The tester should wear gloves to protect his hands from the hot metal.
- After 100 rounds have been fired through each firearm, remove the firearms from the conditioning chamber, disassemble, thoroughly inspect, clean and lubricate.

Data Required:

- Record temperature and exposure times
- Record all malfunctions.
- Record damage noted during inspection
- Record all necessary maintenance actions performed

TLW0010AI - Cold Function Test:

This test evaluates the effect of extreme low temperatures on the functioning performance of the firearms. Shoot the firearm from inside the environmental test cabinet in the long range.

Method:

J.R.Snedeker

Page 42 of 62

03/31/00

Revision #2

ET07373

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Condition the firearm and 100 rounds of ammunition of climatic chamber for at least 6 hours at a temperature of -20 degrees F.
- Test each firearm within the chamber as follows:
- Fire 20 rounds of ammunition. Wait 2 hours and repeat until all 100 rounds have been fired.
- Do not perform maintenance during the 100 round cycle.
- Cycle the safety from fire to safe every 5 rounds.
- After 100 rounds have been fired through the firearm, remove the firearm from the conditioning chamber, disassemble, thoroughly inspect, clean and lubricate.

Data Required:

- Record temperature and exposure times
- Record all malfunctions.
- Record damage noted during inspection
- Record all necessary maintenance actions performed

TLW0010AJ - Thermal Cycle Test

This test evaluates the effects of large temperature changes due to expansion and contraction differentials of metallic and non-metallic components used in the Model 710. The sample rifle will be alternately cycled between a temperature of 120°F. and -20°F. for at least 3 complete cycles, brought back to ambient temperature and test fired in the test jacks for 200 rounds to evaluate both function and safety related characteristics.

Method:

- Shoot sample rifle in test jack to determine rifles malfunction characteristics and rate.
- Do not clean rifle
- Place rifle in freezer that is pre-set to -20°F and leave undisturbed for at least 24 hours.
- At completion of 24+ hours, remove rifle and immediately place in the pre-heated test chamber at a temperature as close to the +120°F as can be attained by the equipment. Leave rifle undisturbed for at least 24 hours.

J.R.Snedeker

Page 43 of 62

03/31/00

Remington Confidential

Revision #2

ET07374

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- At completion of at least 24 hours, remove rifle and immediately place in the freezer.
- Repeat this cycle for a minimum of three complete hot and three complete cold cycles.
- At the completion of the final cycle (the heat cycle) remove the rifle from the chamber and allow cooling to ambient temperature – a minimum of six hours.
- Inspect the rifle for any indications of damage due to the thermal cycling.
- Return the rifle to the test jack used at the start of the test and fire another 100 rounds recording malfunction types and rates.
- Remove the action from the stock and examine the rifle for any obvious signs that the thermal cycling has affected the parts with special attention directed at the metallic and non-metallic interfaces. Look for cracked parts and for signs of material creep.

Data Required:

- Rifle serial number
- Cycle time for each test condition
- Temperature records throughout each cycle. Use the chart feature on the freezer and a temperature-recording device for the chamber.
- Malfunctions type and rates both pre- and post thermal cycles.
- Observations made on cracks, creep or other noteworthy items.

TLW0010AK - Heat & Humidity Function Test:

Method:

- Shoot the firearm from inside the environmental test cabinet in the long range.
- Store the gun and ammunition for a minimum of six hours at a temperature of +100°F and 80-90% Relative Humidity.
- Shoot 100 rounds and record all malfunctions or other unusual events.

Data Required:

- Record temperature and exposure times
- Record all malfunctions.

J.R.Snedeker

Page 44 of 62

03/31/00

Revision #2

ET07375

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Record damage noted during inspection
- Record all necessary maintenance actions performed

DEBRIS TESTING - TLW0010AL THROUGH TLW0010AN

TLW0010AL - Dynamic Sand & Dust Test:

This test evaluates the effects of blowing sand and dust on firearm performance, but the test firing is conducted after the firearm is removed from the sand and dust environment. Use the same sand and dust mixture used in the Sand and Dust Test,

(See Table No. 1.)

Method:

- Clean and lubricate one test firearm and close the muzzle with tape.
- Close the bolt. Set the safety in the SAFE position. Load the firearm using one primed case.
- Expose the firearm as follows:
- Place the firearm in the center of the box, and fasten the box lid.
- After 1 minute, stop the blowing air, remove the lid, and turn the firearm upside down in the box. Replace the lid and repeat the sand and dust blast for another minute.
- Remove the gun from the box after first attempting to wipe clean the firearm with gloved hands. Clean parts as much as possible by blowing the rifle with compressed or shaking the firearm. Carefully remove the tape from the muzzle. REMEMBER THAT THE RIFLE HAS A PRIMED CASE IN THE CHAMBER.
- Take the rifle to a test jack in the short range.
- Place the Safe in the fire position and attempt to fire the round. Make one attempt only. If the primed case does not fire, carefully open the action and remove the primed case, dispose of properly.
- Load the magazine with live rounds and fire a full magazine from the firearm while in the test jack.
- If firing is unsatisfactory, attempt to fire with a clean magazine loaded with clean ammunition. If repeated malfunctions make it impossible to fire all of the ammunition, field strip and clean the firearm in accordance with the applicable operator's manual. Then attempt to fire the remaining ammunition, (from a box of 20

J.R.Snedeker

Page 45 of 62

03/31/00

Revision #2

ET07376

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

cartridges.) If repeated malfunctions make it impractical to fire the remaining ammunition, stop the test. Cycle the safety from fire to safe every 5 rounds.

- At every 5 round interval verify the firearm is not loaded.
- Close the firearm as if to fire it and put the safety to the SAFE position
- Pull the trigger firmly (10 lb. maximum) - firearm must not fire.
- With the finger off the trigger, move the safety to the FIRE position - firearm must not fire.
- Disassemble the firearm over a large white paper and weigh the amount of debris present in the main mechanism

Data Required:

- Record malfunctions.
- Record number of rounds fired.
- Record weight of debris found in the gun.
- Record any firing of the firearm without the trigger being pulled.
- Record any misfires.

TLW0010AM - Stuff Sand & Dust Test:

This test is the second of two that evaluates the effect of sand and dust on firearm performance, where the test firing is conducted after the firearm has sand and dust directly placed in the action. Thus, an exposure box is not required. For Sand & Dust composition see Table No. 1.

Method:

- Clean and lubricate one test gun to the procedure supplied by the design team.
- Remove the bolt. Set the safety in the SAFE position and verify that the firearm is unloaded.
- Record the weight of one level tablespoon of debris mixture.
- Expose the firearm as follows:
- Place the firearm in a shooting jack, bottom of rifle up, and apply a tablespoon of sand in the firecontrol mechanism from the bottom. Tap the firearm three times, in the middle of the receiver, to jar the rifle and to assist getting sand into the mechanism.

J.R.Snedeker

Page 46 of 62

03/31/00

Remington Arms Company Inc. Confidential

Revision #2

ET07377

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Turn the firearm to its normal upright horizontal position and apply a tablespoon of sand and dust to the top of the firecontrol mechanism from the top. Tap the firearm three times, in the middle of the receiver, to jar the rifle and aid sand getting into the mechanism.
- Replace the bolt. Wipe away any sand that prevents the bolt from closing.
- Load the magazine. Fire a full magazine from the firearm. If there are repeated malfunctions, attempt to fire with another magazine. If firing is still unsatisfactory, attempt to fire with a clean magazine, container, etc., loaded with clean ammunition. If repeated malfunctions make it impractical to fire the remaining ammunition (from a box of 20 cartridges), stop the test.
- At every 5 round interval verify the firearm is not loaded.
- Close the firearm as if to fire it and put the safety to the SAFE position.
- Pull the trigger firmly (10 lb. maximum) - firearm must not fire.
- With the finger off the trigger, move the safety to the FIRE position - firearm must not fire.
- Carefully disassemble the firearm over large sheet of white paper and weigh the amount of debris that finds its way into the main mechanism area.

J.R.Snedeker

Page 47 of 62

03/31/00

Remington Confidential

Revision #2

ET07378

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TABLE No. 1. COMPOSITION OF SAND AND DUST MIXTURE

(by percent particles, by weight, retained in sieves)

<u>Sieve Size (US gage sieve no.)</u>	<u>Percent of weight</u> <u>retained</u>	<u>Particle Size</u> <u>(microns)</u>
20	3	842 to 1000
30	5	595 to 841
45	17	355 to 595
60	14	251 to 354
100	10	150 to 250
pass 100	less than 100	
140-mesh silica flour		
140	1	105 to 149
200	4	74 to 105
325	7.5	44 to 74
pass 325	37.5	less than 44

Data Required:

- Record malfunctions.
- Record number of rounds fired.
- Record weight of debris found in the gun.
- Record any firing of the firearm without the trigger being pulled.
- Record any hang fires.

J.R.Snedeker

Page 48 of 62

03/31/00

Remington Confidential

Revision #2

ET07379

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AN - Field Debris Test:

This test determines the effect of "field debris" on firearm performance, where the firing is conducted after the firearm has field debris directly placed in the action. *See Table No. 2 for field debris composition.*

Method:

- Clean and lubricate one test gun to the procedure supplied by the design team.
- Remove the bolt. Set the safety in the SAFE position and verify that the firearm is unloaded.
- Record the weight of one level tablespoon of field debris mixture per following table.
- Expose the firearm as follows:
 - Place the firearm in a shooting jack, turn bottom side up, and apply a tablespoon of debris in the firecontrol mechanism from the bottom. Tap the firearm three times, in the middle of the receiver, to jar the rifle and aid field debris getting into the mechanism.
 - Turn the firearm to its normal upright horizontal position and apply a tablespoon of field debris to the top of the firecontrol mechanism from the top. Tap the firearm three times, in the middle of the receiver, to jar the rifle and aid the debris getting into the mechanism.
- Wipe away any debris that prevents the bolt from closing. Clean parts as much as possible by blowing sharply or wiping.
- Fire a full magazine from the firearm. If repeated malfunctions make this impossible, attempt to fire with another magazine. If firing is still unsatisfactory, attempt to fire with a clean magazine, container, etc., loaded with clean ammunition. If repeated malfunctions make it impractical to fire the remaining ammunition (from a box of 20 cartridges), stop the test.
- Cycle the safety from fire to safe every 5 rounds.
- At every 5 round interval verify the firearm is not loaded.
- Close the firearm as if to fire it and put the safety to the SAFE position
- Pull the trigger firmly (10 lb. maximum) - firearm must not fire.
- With the finger off the trigger, move the safety to the FIRE position - firearm must not fire.

J.R.Snedeker

Page 49 of 62

03/31/00

Revision #2

ET07380

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Disassemble the firearm over white paper and weigh or measure the amount of debris present in the main mechanism area. Debris should be removed from the parts for weighing.

Data Required:

- Record malfunctions.
- Record number of rounds fired.
- Record weight of debris in the gun at the conclusion of the test.
- Record any firing of the firearm without the trigger being pulled.
- Record any hang fires.

Table No. 2 - Field Debris Mixture (By Volume)

Dried Grass Clippings	2 parts
Toothpicks (round, .25" long max.) to represent twigs	1 part
Bird Seed	1 part
Table Salt	1 part
Small Stones (.015" dia. to .125" dia.)	1 part
Crushed Dry Leaves	2 parts
Fine Needles	1 part
Hair Samples (no longer than 2 inch)	1 part

MISC. TESTS - TLW0010AO THROUGH TLW0010AP

TLW0010AO - Rain Test:

Use Standard Remington Rain test procedure using the Salt Fog Chamber.

Rifle must function without any safety related malfunctions.

J.R.Snedeker

Page 50 of 62

03/31/00

Remington Arms Company Inc.

Revision #2

ET07381

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AP - Solvent Testing:

For any non-metallic components in the M/710 that have not previously been tested for the effect of solvents, use Remington standard procedure to solvent test these new components. For some components where there is not enough material in one gun to properly test the sample, secure additional components from Design to complete the testing. If there are components that require testing then use the following procedure:

Tests will be conducted in accordance with ASTM D543-87, which calls for 24-hour immersion in solvents followed by a property evaluation. Hardness or stiffness is the property measured for this test, either quantitatively or qualitatively (where quantitative measurements were impractical). Solvent effects in polymers range from no effect to complete decomposition. Parts that absorb solvents may permanently discolor, crack, craze, or otherwise display failures. The parts also may simply take up solvent when immersed and yield the solvent back when exposed to air with no other property change other than temporary modulus (stiffness) reduction. To support this observation, it is often helpful to separate parts by their amount of solvent uptake, so that the large solvent uptake parts can be more carefully examined.

The receiver insert will be specifically tested for this DAT.

Method:

Obtain untested chemicals.

- Weigh and obtain hardness readings on the test specimen(s).
- Place the specimen(s) in a container so that they are completely covered by the solvent. Leave at rest in the container for 24 hours.
- Remove and wipe the specimen(s) until they are dry. Weigh and obtain hardness readings on the test specimen(s).
- Leave the specimen(s) to air dry an additional 24 hours. Weigh and obtain hardness readings on the test specimens.
- The list of solvents, lubricants and production chemicals commonly used with and around firearms is found in below:

Remington Oil
Remington Bore Cleaner

J.R.Snedeker

Page 51 of 62

03/31/00

Remington is a registered trademark

Revision #2

ET07382

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Break Free Bore Cleaner
Birchwood-Cassey Gunscrubber
Remington Action Cleaner
Hoppe's Oil
Hoppe's #9 Solvent
TPC Solvent
LP-1 Lubricant
Thin Film Lubricant
Steel Guard
Molycoat Paste
Molycoat Powder
Cobratex

Data Required:

- Record part weights before and after test.
- Record part hardness before and after test.

ABUSIVE TESTING

IMPACT TESTING - TLW0010AQ THROUGH TLW0010AV

TLW0010AQ - SAAMI Drop Test:

This test will simulate abusive dropping of the firearm from a distance of 48 inches onto a 1" thick 85 durometer (Shore A) rubber mat backed by concrete. Trigger Pull weight will be adjusted to minimum specification (3-1/2 lb.) The Trigger/Sear engagement will be set to the minimum specification (0.020"). Test will be performed according to SAAMI Technical Committee procedures. Magazine capacity will as well be according to SAAMI procedures. After each series of test, the primed case will be discharged to insure validity of test. This test will be performed on a sample of four firearms (for Phase I) and six firearms (Phase II) of .30-06 calibers only and six rifles of .270 caliber when available.

Method:

- With the firearm safety in the SAFE state, the firearm shall be capable of passing the below test criteria for drop testing from a height of four feet onto an 85±5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun is dropped it will fall and

J.R.Snedeker

Page 52 of 62

03/31/00

Remington Confidential

Revision #2

ET07383

CONFIDENTIAL

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

come to rest without interference within the perimeter of the mat. The four feet shall be measured from the surface of the rubber mat to the center of gravity of the firearm. The center of gravity shall be determined to an accuracy of \pm one inch by any recognized method for finding the center of gravity of an irregular shaped object. The primed case shall be discharged following the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.

- The firearm or firearms shall be dropped in such a way as to strike the rubber mat surface once in each of the following attitudes:
 - Barrel vertical, muzzle down.
 - Barrel vertical, muzzle up.
 - Barrel horizontal, bottom up.
 - Barrel horizontal, bottom down.
 - Barrel horizontal, left side up.
 - Barrel horizontal, right side up.
- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol lubricated as in the owner's manual.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges and inserted in the firearm.
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks - replace before continuing test.

Data required:

- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record round level

J.R.Snedeker

Page 53 of 62

03/31/00

Remington Confidential

Revision #2

ET07384

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AR - SAAMI Jar-Off Test:

The objective of the jar-off test is to simulate the abusive impacting (bumping) of the firearm against a hard surface with the firearm in a condition of maximum readiness. With the firearm in the ready to fire condition, the firearm shall be capable of withstanding a jar-off shock equivalent to being dropped from a height of 12" inches onto a 1" thick 85 Durometer (Shore A) rubber mat backed by concrete. Trigger Pull weight will be adjusted to minimum specification. The test will be performed according to SAAMI Technical Committee procedures. Magazine will be loaded to maximum capacity with dummy rounds according to SAAMI procedures. A fresh primed case will be chambered prior to each drop. After each drop the primed case will be discharged to verify its validity. This test will be performed on a sample of firearms made up of .30-06 caliber.

Method:

- With the firearm cocked and the safety in the FIRE position the firearm shall be capable of withstanding jar-off shock equivalent to being dropped from a height of twelve inches onto a 85±5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun is dropped it will fall within the perimeter of the mat striking the mat once. The twelve inches will be measured from the test surface to the lowest point on the firearm. As an alternate to free dropping, other methods may be substituted if they provide equivalent impact characteristics. The primed case shall be discharged following the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.
- The firearm or firearms shall be dropped in such a way as to strike the rubber mat surface once in each of the following attitudes:
 - Barrel vertical, muzzle down.
 - Barrel vertical, muzzle up.
 - Barrel horizontal, bottom up
 - Barrel horizontal, bottom down.
 - Barrel horizontal, left side up.
 - Barrel horizontal, right side up.

J.R.Snedeker

Page 54 of 62

03/31/00

Remington Arms Company Inc.

Revision #2

ET07385

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol lubricated per the owner's manual.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges and inserted in the firearm.
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks - replace before continuing test.

Data required:

- Record engagement and trigger pull.
- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record the round level on the firearm.

TLW0010AS - SAAMI Rotation Test:

The test will be conducted according to SAAMI Technical Committee procedures. The firearm will be placed in the "Safe Carrying" condition and dropped from an upright position with its butt resting on the surface of a 1 1/2 inch 85 Durometer (Shore A) rubber mat backed by concrete. Trigger Pull weight will be adjusted to minimum specification. Magazine capacity will as well be according to SAAMI procedures. The firearm shall be tested (dropped) on both the right and left sides. After each rotation, the primed case will be discharged to insure validity of test.

Method:

- With the firearm safety in the SAFE state, the firearm shall be capable of passing the below test criteria when allowed to fall freely from an upright position with its butt resting on the surface of a 85±5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun falls it will come to a rest without interference within the perimeter of the mat. The firearm shall be tested so as to fall once on its right-hand side and once on its left-hand side. The primed

J.R.Snedeker

Page 55 of 62

03/31/00

Remington Arms Company

Revision #2

ET07386

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

case shall be discharged following the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.

- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol lubricated per the owner's manual.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges, inserted in the firearm.
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks, replace before continuing test.

Data required:

- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record round level on the firearm

TLW00104T- Extended SAAMI Jar-Off Test: (for Information only.)

With the intent to establish design margin this test simulates the abusive impacting (bumping) of the firearm against a hard surface with the firearm in a state of maximum readiness under conditions more severe than the SAAMI recommendations. This test will be performed on a sample of six (Phase II) (or the number available after performing the std. SAAMI tests) firearms.

Method:

- With the firearm cocked and in the safety in the FIRE position the firearm shall be dropped from a height of 18 inches, 24 inches, and 48 inches onto a 85 ± 5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun is dropped it will fall within the perimeter of the mat striking the mat once. The distance of drop will be measured from the test surface to the lowest point on the firearm. The primed case shall be discharged following

J.R.Snedeker

Page 56 of 62

03/31/00

Revision #2

ET07387

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.

- The firearm or firearms shall be dropped in such a way as to cause it to strike the rubber mat surface in each of the following attitudes:

- Barrel vertical, muzzle down.
- Barrel vertical, muzzle up.
- Barrel horizontal, bottom up
- Barrel horizontal, bottom down.
- Barrel horizontal, left side up.
- Barrel horizontal, right side up.

- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol well lubricated with Rem-Oil.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges and inserted in the firearm.
- Conduct this test at 18 inches, 24 inches, and 48 inches.
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks - replace before continuing test.

Data required:

- Record engagement and trigger pull
- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record the round level on the firearm

J.R.Snedeker

Page 57 of 62

03/31/00

Remington Confidential

Revision #2

ET07388

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AU - Extended SAAMI Rotation Test: (for Information only.)

With the intent to establish design margin this test simulates the abusive fall of a firearm when left leaning against a vertical surface under conditions more severe than the SAAMI recommendations. This test will be performed on a sample of six (Phase II) (or of those still available) firearms.

Method:

- With the firearm safety in the SAFE state, the firearm shall be capable of passing the following test criteria when allowed to fall freely from an upright position with its butt resting on the surface of a tiled floor backed by concrete. The firearm shall be tested so as to fall once on its right-hand side and once on its left-hand side. The primed case shall be discharged following the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.
- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol well lubricated with Rem-Oil.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges, inserted in the firearm.
- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks - replace before continuing test.

Data required:

- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record round level of the firearm.

Snedeker

Page 58 of 62

03/31/00

Revision #2

ET07389

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

TLW0010AV – Extended SAAMI Drop Test: (for Information only)

With the intent to establish design margin this test simulates abusive dropping of the firearm in conditions more severe than the SAAMI recommendations. This test will be performed on a sample of six (or of those still available) firearms.

Method:

- With the firearm safety in the SAFE state, the firearm shall be dropped from a height of 6 feet and 8 feet onto a 85 ± 5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun is dropped it will fall and come to rest without interference within the perimeter of the mat. The drop height shall be measured from the surface of the rubber mat to the center of gravity of the firearm. The center of gravity shall be determined to an accuracy of \pm one inch by any recognized method for finding the center of gravity of an irregular shaped object.
- The primed case shall be discharged following the drop and a fresh primed cartridge re-chambered prior to the next drop. A "fresh" firearm may be substituted into the test at any point.
- Test Procedure: The firearm or firearms shall be dropped in such a way as to strike the rubber mat surface once in each of the following attitudes:
 - Barrel vertical, muzzle down.
 - Barrel vertical, muzzle up.
 - Barrel horizontal, bottom up.
 - Barrel horizontal, bottom down.
 - Barrel horizontal, left side up.
 - Barrel horizontal, right side up.
- Tests shall be conducted with the trigger pull force set at the minimum force specified, with engagement set to the minimum specified, and with the firecontrol well lubricated with Rem-Oil.
- The test shall be conducted with the magazine or clip fully loaded with dummy cartridges and inserted in the firearm.

J.R.Snedeker

Page 59 of 62

03/31/00

Confidential

Revision #2

ET07390

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Parts breakage or other damage as a result of drop testing does not constitute failure as long as the empty primed case does not fire and the firearm can be unloaded safely after each drop. More stocks are required than the amount of test guns to allow for breakage due to the drop testing. If a stock cracks - replace before continuing test.

Data required:

- Record whether or not the firearm fires an empty primed case of its designated cartridge when tested in accordance with this procedure.
- Record round level on the firearm.

INTENTIONAL ABUSE- TLW0010AW THROUGH TLW0010AY

Note that for all of the following tests, the rounds are to be loaded remotely and the test setup shall have the capability of unloading live rounds remotely if required.

TLW0010AW - Pierced Primer Test:

For this test, a firing pin will be altered to have a "wedge-shaped" point. This type of firing pin point should produce a pierced primer when fired. The purpose of piercing the primer is to allow high-pressure gases to escape into the action and thereby determine the effect of high-pressure gases when dumped into the bolt, magazine box and receiver areas. All standard Remington high-pressure ammunition safety procedures will be used for this test. A standard round of .30-06 ammunition will be used.

After firing the rifle will be examined for damage. Photographs of damaged components will be taken and kept for record. The rifle will be tagged and saved for possible future review.

Method:

- Position firearm in test jack located in the "Blow-up" room with the muzzle through the port.
- Set witness paper at the rear of the action perpendicular to the bore.
- Locate witness paper at the approximate location expected for the shooter's face.
- Set up the High Speed Video to tape the firing test.
- Fasten a lanyard around the stock and run through the trigger guard in front of the trigger.

J.R.Snedeker

Page 60 of 62

03/31/00

Revision #2

ET07391

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Load a standard factory .30-06 round into the chamber, and carefully close the bolt.
- All personnel are to leave the room.
- When ready to conduct the test start the high speed video and pull the lanyard.
- Carefully examine the scene looking for any broken or missing parts, holes in the witness paper etc.

Data Required:

- Rifle serial number.
- The condition of the witness paper.
- Notes of any broken or missing parts.
- Photographs of broken or missing parts.

TLW0010AX - High Pressure Test:

The rifle will be tested to 120,000 psi. The purpose of this test is to determine the extent of damage if an individual does purposely or accidentally handload an extremely high pressure load. Use standard Remington high-pressure ammunition safety procedures for these tests. The pressures for the test round will be worked up using various grain size loads giving pressures below 95,000 psi, (approaching the limits of the transducer gauges). The grain size load will be plotted and a curve extrapolated to determine the load expected to produce a load of approximately 120,000-psi.

All testing will be done in the blow-up room using the high-speed video camera and witness paper. Before removing or otherwise disturbing the test samples after blow-up, photographs will be taken for the record. After collection and removal of the parts additional photographs of the various individual components will be taken for the record. All parts will be put in sample bags, boxed and temporarily stored for review if required.

TLW0010AY - Obstructed Bore Test:

One of the sample rifles will have a rifle bullet driven into the bore to a position immediately ahead of the chamber. A standard round (.30-06, 220 gr. factory load) will be loaded and fired remotely. All testing will

J.R.Snedeker

Page 61 of 62

03/31/00

Remington - Confidential

Revision #2

ET07392

Confidential - Subject to Protective Order
Williams v. Remington

Remington Arms Company Inc.

RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

be done in the blow-up room using the high-speed video camera and witness paper. Before removing or otherwise disturbing the test samples after blow-up photographs will be taken for the record. After collection and removal of the parts additional photographs of the various individual components will be taken for the record. All parts and will put in sample bags, boxed and temporarily stored for review if required.

CONFIDENTIAL 83

J.R.Snedeker

Page 62 of 62

03/31/00

Remington Confidential

Revision #2

ET07393

Confidential - Subject to Protective Order
Williams v. Remington