

P.I. No GUN EXAMINATION REPORT NUMBER: _____ MODEL: 700

GENERAL CONDITION: GOOD R #: 005424

OUTSIDE WORK: TRIGGER STOP SCREW SEAL DATE: 2-25-72

FROM: DONALD GAGNON
CHICAGO, ILLINOIS

FIRED AMMO TYPE: —

GUN #: 6362419

& CONDITION: _____
ASSEMBLER V

PROOF: R.E.P.-A INSP.: 58 TEST: 13

CODE: DT-9/70

HEADING: _____

GA./CAL.: 300G SPR.

BREECH OPENING: —

CHECKED BY: C. PROSSER

RECOIL SHOULDERS: _____

APPROVED: _____

CHAMBER: O.K.

APPROVED: _____

TEST: NO

APPROVED: _____

COMPONENT CONDITION: (Damaged, Broken, Old Style) APPROVED: _____

NO DAMAGED COMPONENTS. HORIZONTAL ENGAGEMENT
.030 MIN. = .020 CONNECTOR CLEARANCE ON TRIGGER =
1.072 MID = ^{1.079} 1.076 TRIGGER CLEARANCE ON CONNECTOR =
1.089 MID = ^{1.083} 1.080. TRIGGER STOP SCREW SEAL BROKEN.
TRIGGER BIND DETECTABLE, LUBRICANT TOO HEAVY.

COMPLAINT: FIRES WHEN SAFETY IS RELEASED.

INCIDENT: TRIGGER FAILS TO RETRACT.

COMMENTS: THE FIT OF THE TRIGGER TO THE HOUSING, TOO
HEAVY LUBRICANT & EXCESS CLEARANCE BETWEEN
CONNECTOR AND TRIGGER (.010) COULD LEAD TO THE
CUSTOMER'S MALFUNCTION.