

Remington Arms Company
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
EUzabethtown, KY 42701

# **ACCURACY TESTING:**

## ACCURACY AND POLITESTING - TLW0300AC THROUGH TLW0300AF

#### TLW0300AC - POI & Group Size - Initial Test with High Quality 36X Scope:

The point of impact test involves the verification of the firearms sighting system adjustment and the potential to hit the point of aim. Random variation and/or extreme difference in shot to shot point of impact (as well as group size) typically indicate improper barrel processing and is used as a final inspection flag in production. Shoot three, 5-shot groups from each test rifle. Use the same code of ammunition for all point of impact test shots.

#### Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Pick the point of aim on the target
- Adjust point of aim to the bulls-eye at 100 yards.
- Shoot five "warmer" shots
- Shot three, 5-shot groups.

### Data Required:

- Measure the center of the impact groups to the point of aim in terms of "x" and "y" positions.
- Record takedown screw torque
- Record ammunition lot number used during the test
- · Record and label any fail-to-fire armunition

J.R. Snedeker

Page 34 of 51

9:45 AM 9/21/00

**TLW0300** 

Remington Confidential

Revision # 0

Subject to Protective Order - Williams v. Remington