

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

actual targets and recorded. The same code of ammunition and same type of ammunition will be used for all group size test shots. Average group sizes must be $\leq 3"$ at 100 yards.

Method:

- Certify the ammunition selected for muzzle velocity and pressure.
- Fire three, 5-shot groups at 100 yards, for each ammunition type selected. Prior to beginning of the test, clean the bore and shoot 5 "fouling" shots to seat in the rifle.
- Cycle the safety from fire to safe every 5 rounds.
- Accuracy should be shot from a recoiling rest. Shoulder shooting is acceptable but not the preferred way.

Data Required:

- Measure group sizes center to center
- Record takedown screw torque
- Record make and identifier of scope
- Record ammunition type used.
- Record ammunition lot numbers used during the test
- Record and label any fail-to-fire ammunition.
- Record any malfunctions that occur during the test.

J.R.Snedeker

Page 37 of 51

9:45 AM 9/21/00

TLW0300

Remington Confidential

Revision # 0

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R0002968

ETE00002967