

Cast. Complaint ✓

P.I. No GUN EXAMINATION REPORT NUMBER: _____ MODEL: 700

GENERAL CONDITION: FAIR R #: 11955

OUTSIDE WORK: SCOPE MOUNTED DATE: 6-3-71

FROM: NATIONAL PARK SERVICE,

FIRE AMMO TYPE: - KAHULUI MAUI, HAWAII

& CONDITION: _____ GUN #: 6258362

ASSEMBLER 64

PROOF: R.E.P.-E INSP.: U TEST: 87 CODE: 05 = 7/69

HEADING: O.K. GA./CAL.: 3006

BREECH OPENING: - CHECKED BY: C. PROSSER

RECOIL SHOULDERS: O.K. APPROVED: _____

CHAMBER: O.K. APPROVED: _____

TEST: No APPROVED: _____

COMPONENT CONDITION: (Damaged, Broken, Old Style) APPROVED: _____

No BROKEN, ETC. COMPONENTS.

CONNECTOR CLEARANCE ON TRIGGER = 1.070 M/D = ^{1.079}1.076 - .006

TRIGGER CLEARANCE ON CONNECTOR = 1.089 M/D = ^{1.083}1.080 + .006

CONNECTOR-SEAR ENGAGEMENT = .020, EXCESSIVE

LUBRICANT AND DIRTY, TRIGGER PULL FOUR POUNDS.

COMPLAINT: FIRE WHEN SAFETY IS PUSHED OFF.

INCIDENT: TRIGGER CONNECTOR FAILED TO RETRACT.

COMMENTS: CAN NOT DUPLICATE CUSTOMER'S MALFUNCTION.

THE TRIGGER & TRIGGER CONNECTOR NOT TO MODEL

DRAWING PERMIT SEAR-TRIGGER CONNECTOR INTERFERENCE,

FAILURE TO RETRACT.