

PROJECT# 241095		D.A.T.(2)	
SAAMI DROP TEST. TLW 0010AQ			
SAAMI JAR-OFF TEST. TLW 0010AR			
SAAMI ROTATION TEST. TLW 0010AS			
JAR-OFF TEST		POSITION	
12 IN / SAFE OFF	BARREL HORIZONTAL, BOTTOM OF STOCK DOWN		
12 IN / SAFE OFF	BARREL HORIZONTAL, BOTTOM OF STOCK UP		
12 IN / SAFE OFF	BARREL HORIZONTAL, LEFT SIDE OF STOCK UP		
12 IN / SAFE OFF	BARREL HORIZONTAL, RIGHT SIDE OF STOCK UP		
12 IN / SAFE OFF	BARREL VERTICAL, MUZZEL UP		
12 IN / SAFE OFF	BARREL VERTICAL, MUZZEL DOWN		
DROP TEST		POSITION	
48 IN / SAFE ON	BARREL HORIZONTAL, BOTTOM OF STOCK DOWN		
48 IN / SAFE ON	BARREL HORIZONTAL, BOTTOM OF STOCK UP		
48 IN / SAFE ON	BARREL HORIZONTAL, LEFT SIDE OF STOCK UP		
48 IN / SAFE ON	BARREL HORIZONTAL, RIGHT SIDE OF STOCK UP		
48 IN / SAFE ON	BARREL VERTICAL, MUZZEL UP		
48 IN / SAFE ON	BARREL VERTICAL, MUZZEL DOWN		
ROTATION TEST		POSITION, SAFE ON	
FIREARM VERTICAL DROP SO LEFT SIDE OF STOCK IS UP			
FIREARM VERTICAL DROP SO RIGHT SIDE OF STOCK IS UP			
EXT JAR-OFF		POSITION	

BARBER - 5.30.060006078

ETE00003038