

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

Break Free Bore Cleaner
Birchwood-Casey Gunscrubber
Remington Action Cleaner
Hoppe's Oil
Hoppe's #9 Solvent
TPC Solvent
LP-1 Lubricant
Thin Film Lubricant
Steel Guard
Molycoat Paste
Molycoat Powder
Cobratex

Data Required:

- Record part weights before and after test.
- Record part hardness before and after test.

ABUSIVE TESTING**IMPACT TESTING – TLW0010AQ THROUGH TLW0010AV****TLW0010AQ - SAAMI Drop Test:**

This test will simulate abusive dropping of the firearm from a distance of 48 inches onto a 1" thick 85 durometer (Shore A) rubber mat backed by concrete. Trigger Pull weight will be adjusted to minimum specification (3-½ lb.) The Trigger Sear engagement will be set to the minimum specification (0.020"). Test will be performed according to SAAMI Technical Committee procedures. Magazine capacity will as well be according to SAAMI procedures. After each series of test, the primed case will be discharged to insure validity of test. This test will be performed on a sample of four firearms (for Phase I) and six firearms (Phase II) of .30-06 calibers only and six rifles of .270 caliber when available.

Method:

- With the firearm safety in the SAFE state, the firearm shall be capable of passing the below test criteria for drop testing from a height of four feet onto an 85±5 Durometer, Shore A, rubber mat, one-inch thick backed by concrete. The mat and concrete shall be large enough so that when the gun is dropped it will fall and

J.R. Snedeker

Page 52 of 62

03/31/00

Remington Confidential

Revision #2