

Microsoft Access

File Edit View Records Window Help

Customer Service Data Entry

File Number: 109 Ams Service number: 9703679

Last Name: BEELER First Name: HERMAN

Street: 58045 WASHINGTON SPRINGS RD City: GLADE SPRING

State: VA Zip: 24340 Home Ph:

Work Ph: Product Type: F A T O

Type Concern: S PI PD P S C Concern Code: 1007

Concern: FIRED ON SAFE RELEASE

Cause Code: 4030 Cause: NO FAULT FOUND

Assigned To: KAST Classification: UNC UNJ UNC UND J

Settlement Detail: REPLACE TRIG N/C Settlement Amount: \$0.00

Date Opened Rem: 2/10/97 Date Opened by P/S: 2/10/97 Caliber: 243

Date of Incident: Date Closed: 2/10/97 Bullet Weight:

Date to Analysis: Date from Analysis: Manufacturer: REM

Model: 700 Serial: 06578966 Date Code: WK Date Mfgd: 8/1790

RAMAC: 700 Litigation: ☐ PreLitigation: ☐ Obsolete: ☐

Custody: ☐ Comments: OVER MAX SEAR ENGAGEMENT TRIG PULL AT MAX

Time of Modification: 2:15:30 PM Date of Modification: 2/10/97

Form View FLTR CAPS NUM

RECEIVING AND ESTIMATING REPORT

COMMENT:

ORDER

R 97-03679

INITIAL CUSTOMER ORDER NO.

PRODUCT SERVICE

DATE RECEIVED

DATE OPENED

DATE CODE

SERIAL NUMBER

NEW SERIAL NUMBER

MODEL AND GRADE

02/03/97

02/10/97

WK 8-90

C6578966

700 243

ADL

ACCESSORIES

W/STUDS

FROM:

SHIP TO:

BEELER, HERMAN
36045 WASHINGTON SPRINGS RD
GLADE SPRING VA 24340

BEELER, HERMAN
36045 WASHINGTON SPRINGS RD
GLADE SPRING VA
24340

ACCOUNT NUMBER

ACCOUNT NUMBER N/C

CUST NO: 161769 C.B.D.

WRITE ☐

PRCM DATE

ESTIMATED

VIA

UPS

GUN CONDITION

- ☐ NEW
☐ LIGHTLY WORN
☐ WORN
☐ VERY WORN
☐ UNREPAIRABLE
☐ MARRED

REPAIR CHARGE

EXCISE

TAX

INSURANCE

UPS

PARCEL POST

TOTAL

CUSTOMER CONCERN

AMMO

FUNCTION

FINISH

ACCURACY

FIT

INSPECT

CYCLE

TRIGGER GROUP

BOLT ASSY.

BARREL ASSY.

REC. ASSY.

WOOD

METAL

MAIN FAULT.

Found when safe was released

The only way that the gun could be made to fire as needed was with the safe off and the trigger pulled. Took trigger Assy. apart - NO FAULT FOUND. Exchange Trig. Assy. at M/C due to excessive engagement.

PARTS

COMMENTS

Trig. pull 5 1/4 to 5 3/4 lbs as Recd.

Rust on firing pin spring

Safe engagement over max setting.

REPAIRMAN

PRCM

CLEAN

TEST

TARGET

PATTERN

GALLERY TESTER

DATE

DATE

DATE

DATE

DATE

OFFICE COPY

RD6925-4E-11146

The Gun Fired When The
Safety Was Released.

Herman L Beeler