

Remington Confidential

APPROVALS.....	4
INTRODUCTION:	5
INITIAL TESTS, MEASUREMENTS AND INSPECTIONS:	6
<i>HEADSPACE AND PROOF - TLW0010A THROUGH TLW0010C:</i>	<i>6</i>
TLW0010A - Measure Headspace	6
TLW0010B - Proof Test	7
TLW0010C - Re-Measure Headspace after Proof	9
<i>FORCES - TLW0010D THROUGH TLW0010K:</i>	<i>10</i>
TLW0010D - Measure Firing Pin Indent:	10
TLW0010E - Measure Scar/Trigger Engagement and Scar Lift	11
TLW0010F - Measure Trigger Pull Forces:	12
TLW0010G - Measure Safe On/Off Forces:	12
TLW0010H - Measure Bolt Lift and Bolt Closing Forces	13
TLW0010I - Measure Magazine Spring Force:	14
TLW0010J - Measure Recoil Force:	15
TLW0010K - Measure Lock Time:	15
<i>WEIGHTS OF MAJOR COMPONENTS - TLW0010L THROUGH TLW0010O:</i>	<i>17</i>
TLW0010L - Overall Weight:	17
TLW0010M - Weight of Stock Assembly:	18
TLW0010N - Weight of Barrel Assembly:	18
TLW0010O - Weight of Bolt Assembly:	19
<i>LENGTHS OF MAJOR COMPONENTS - TLW0010P THROUGH TLW0010R:</i>	<i>20</i>
TLW0010P - Overall Length:	20
TLW0010Q - Barrel Length:	20
TLW0010R - Length of Pull:	21
<i>GUN CHARACTERISTICS - TLW0010S THROUGH TLW0010U:</i>	<i>22</i>
TLW0010S - Balance Point:	22
TLW0010T - Drop and Cast:	23
TLW0010U - 50 lb. Trigger Pull Test:	23
<i>FIREARMS MEASUREMENTS - TLW0010V THROUGH TLW0010Z:</i>	<i>25</i>
TLW0010V - Chamber cast:	25
TLW0010W - Bore Diameter:	25
TLW0010X - Groove Diameter:	26
TLW0010Y - Twist Rate (30-06)	26
TLW0010Z - Magazine Capacity Test:	26