

	A	B	C	D	E	F	G	H	I
1	XR100 DAT A6 MIN								
2	Make:	Model:	Test Nr.	Force	Travel	Take-up	Overtravel	Energy	Lock Time
3	Remington	XR100		[lbs]	[inch]	[inch]	[inch]	[lbs.inch]	[ms]
4	Single Action		1	6.244	0.018	0	0.012	0.073	
5			2	6.156	0.02	0	0.012	0.077	
6			3	6.087	0.018	0	0.013	0.071	
7			4	6.074	0.022	0	0.014	0.086	
8			5	5.998	0.018	0	0.014	0.072	
9			6	6.369	0.022	0	0.013	0.09	
10			7	6.142	0.018	0	0.014	0.072	
11			8	6.047	0.018	0	0.015	0.071	
12			9	6.361	0.018	0	0.014	0.076	
13			10	5.986	0.018	0	0.015	0.069	
14			Avg:	6.146	0.019	0	0.014	0.076	0.00 ms
15									
16	XR100 A7 Fac								
17	Make:	Model:	Test Nr.	Force	Travel	Take-up	Overtravel	Energy	Lock Time
18	Remington	XR100		[lbs]	[inch]	[inch]	[inch]	[lbs.inch]	[ms]
19	Single Action		1	6.571	0.023	0	0.018	0.09	
20			2	6.718	0.018	0	0.026	0.074	
21			3	6.622	0.017	0	0.025	0.068	
22			4	6.692	0.017	0	0.025	0.071	
23			5	6.502	0.019	0	0.026	0.075	
24			6	6.396	0.019	0	0.026	0.076	
25			7	6.493	0.019	0	0.025	0.077	
26			8	6.447	0.016	0	0.025	0.064	
27			9	6.419	0.019	0	0.025	0.073	
28			10	6.545	0.016	0	0.025	0.064	
29			Avg:	6.541	0.018	0	0.025	0.073	0.00 ms
30									
31									
32	TOTAL AVG								
33	Single Action			6.343	0.019	0	0.019	0.074	0.00 ms