

	A	B	C	D	E	F	G	H	I
1	XR100 DAT A6 MIN								
2	Make:	Model:	Test Nr.	Force	Travel	Take-up	Overtravel	Energy	Lock Time
3	Remington	XR100		[lbs]	[inch]	[inch]	[inch]	[lbs.inch]	[ms]
4	Single Action		1	6.244	0.018	0	0.012	0.073	
5			2	6.156	0.02	0	0.012	0.077	
6			3	6.087	0.018	0	0.013	0.071	
7			4	6.074	0.022	0	0.014	0.086	
8			5	5.998	0.018	0	0.014	0.072	
9			6	6.369	0.022	0	0.013	0.09	
10			7	6.142	0.018	0	0.014	0.072	
11			8	6.047	0.018	0	0.015	0.071	
12			9	6.361	0.018	0	0.014	0.076	
13			10	5.986	0.018	0	0.015	0.069	
14			Avg:	6.146	0.019	0	0.014	0.076	0.00 ms
15									
16	XR100 A7 Fac								
17	Make:	Model:	Test Nr.	Force	Travel	Take-up	Overtravel	Energy	Lock Time
18	Remington	XR100		[lbs]	[inch]	[inch]	[inch]	[lbs.inch]	[ms]
19	Single Action		1	3.233	0.022	0	0.032	0.048	
20			2	3.517	0.021	0	0.031	0.049	
21			3	3.499	0.02	0	0.031	0.047	
22			4	3.504	0.021	0	0.031	0.05	
23			5	3.545	0.02	0	0.032	0.048	
24			6	3.412	0.022	0	0.031	0.05	
25			7	3.485	0.02	0	0.031	0.048	
26			8	3.418	0.02	0	0.032	0.046	
27			9	3.498	0.022	0	0.032	0.052	
28			10	3.462	0.022	0	0.031	0.05	
29			Avg:	3.457	0.021	0	0.031	0.049	0.00 ms
30									
31									
32	TOTAL AVG								
33	Single Action			4.802	0.02	0	0.023	0.062	0.00 ms