

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE

Remington
SUPER

PETERS
SUPER

cc. E. C. Hadley
G. O. Clifford, Ilion

Bridgeport, Connecticut, April 3, 1942

RECEIVED: H. A. BROWN

APR 3 1942

TO: H. A. BROWN

FROM: H. D. HERBERT
DEVELOPMENT DIVISION
BUILDING 335

SUBJECT: MODEL 720 SAFETY COMPLAINT

Reference: K.J. Lowe to H.A. Brown - March 26, 1942

We have examined and tried the safety mechanism on the sample #40895, ID-169 and find it to be satisfactory. We believe a further improvement should be made eventually so that the safe can only be all the way on or off, with no middle position possible.

The gun was checked briefly for function and accuracy. Function and grouping were satisfactory, but the gun, as received, shot 6 inches low. The rear sight insert was set very low in the sight causing the trouble.

The stock color happened to be unusually dark brown. H. P. Davis checked this with G. E. Pinckney and C. B. Wells. Pinckney enthused, Wells ok'd.

Function Test:

- 6 - Western 220 gr. Silvertip - ok.
- 6 - Remington 180 gr. S.P. C'kt. - ok.
- 6 - RA - 41 - 150 gr. - ok.

Accuracy: (Open Sights, Muzzle & Elbow - 50 yds.)

Western 220 gr. Silvertip

- a. 6 shots to set sights
- b. 5 shots - E.S. 1.75 in.

H. D. Herbert

For Tech. Dept. approval.

EDH:MEP

4/3. P.M.
B.E. & H.D.
the sample
H.A.B.