

ARMS PRODUCTS COMMITTEE

DATE April 4, 1942

FOR CIRCULATION AND APPROVAL

PLEASE PASS ALONG PROMPTLY

SUBJECT: MODEL 720 - IMPROVEMENT TO SAFETY MECHANISM

NAME

COMMENT AND DATE

1. G. E. Pinckney *has OK'd*
2. C. B. Wells *" "*
3. W. R. Scott
4. R. H. Coleman *OK 4/6/42*  
~~C. Q. Clifford~~  
(extra copy sent to Ilion)
5. A. E. Buchanan *has OK'd 4/4/42*
6. C. M. Green *OK 4/4/42*
7. ~~E. C. Hadley~~ *OK 4/13/42*
8. H. A. Brown *OK 4/4/42*
- ✓ B. E. Strader *has OK'd 4/3/42*
- D. F. Carpenter *OK 4/2/42*
- E. E. Handy *OK 4/2/42*

If you approve signify above by signature or initials; if not, please attach your comment.

INFORMATIVE DATA

In the safety mechanism as previously produced, it was possible to rotate the thumb piece far enough rearward so that the shooter might believe the gun to be safe. However, with the safety in this position after the trigger was pulled, the gun could be discharged by moving the safety to the forward "off" position.

(over)

HAB:MR

*H. A. Brown*