

WJL 721-772 - NORMAN

Make	Detail Price	Dealer's Discount	Jobber's Margin	Cost to Remington	Remarks
Pachmeyer "Lo-Brig"	\$ 20.00	33-1/3%	50%	50 & 10%	Means of Attachment Four (4) screws left side Receiver. (Will jig available - \$6.00 deposit.) Bullet Struck Yes Frontal All scopes not larger than 1" dia. Sampled Being shipped.
(Quotes per their letter 4/23/48)					
Stith "Master"	20.00	33-1/3%	53-1/3%	53-1/3%	Means of Attachment Front - present holes in top of Receiver. side plate furnished to suit present holes at left rear of Receiver - Rear Mount Plate for top Receiver on Request. Bullet Struck Yes Frontal Practically all American Hunting & small game scopes - Specify Band size - 3/4", 7/8", and 1" Sampled Yes on 1/721 No. 23601.
(*) Present terms - subject to change. (All quotes in letter H.J. Stith to S.H. Alvin 4-21-48)					
"C.E.D. Style" (Install-It-Yourself)	15.00	33-1/3%	50%	50%	Means of Attachment Rear Right dovetail slot and present tapped holes - Rear - Left side Receiver. Bullet Struck Yes (?) Frontal Weaver E-2.5; S-4; E-4; E-6 J-2.5 or 330-460 Aluminum - Yes
" (For Weaver J-2.5) 12.00	33-1/3%	50%	50%		Means of Attachment Same as above Bullet Struck Yes (?) Sampled Shipped
"C.E.D. Windage Type" 15.00	33-1/3%	50%	50%		Means of Attachment Same as above. Bullet Struck Yes Frontal Rear-On & Weaver S-4 Sampled Shipped
"Install-It-Yourself" 15.00	33-1/3%	50%	50%		Means of Attachment Same as above. Bullet Struck Yes (?) Frontal Aluminum - Temp & Weaver E-2.5; S-4
Lakley "Snap-On" 14.95	(will advise)				Means of Attachment Present two holes - Top Front Receiver; two holes - top Rear Receiver. Bullet Struck No Frontal 7/8" & 1" Dia. Rings Sampled Yes

MODEL 721-722 - REMINGTON
Sheet 2

Redfield-Jr.	(3/4" Rings) (22mm. Rings) (1" Rings) (26 mm. Rings)	10.75) 12.75) 14.75) 17.75)	33-1/3%	50%	60%	Means of Attachment: Present two holes - Top Front of Receiver; 1 add. hole top Rear Bridge of Receiver. Inlet Stock: No Access to Bolt Ring Sizes: Same as Bolt Ring Sizes Example: Yes
Weaver "Type 'C'"	"Type 'C'"	5.75	3.50-4.20	2.90	2.90	Means of Attachment: Present holes in Receiver Front & Rear Inlet Stock: Yes - for Rear Access: 3/4" Scoops - Any of Weaver type Series. Example: On Hand Means of Attachment: Same Q-14 Front Ring Q-10 Rear Mount B-14 Front Ring B-10 Rear Mount
Griffin & Howe	"Type 'D'"	6.25	3.80-4.60	3.20	3.20	Inlet Stock: Yes - Rear Access: 1" Scoops; Any of Weaver type Series. Means of Attachment: Flush Pinned (Milled) to Left Side of Receiver. Inlet Stock: Yes Access: Alaskan - Tamm, etc. Requires Special Tooling to fit. Remington not equipped.
Williams "QC"	"QC"	17.50	33-1/3% (1 to 12) 40% (more than 12)	50% A 25 But 10	50% A 25 But 10	Means of Attachment: Uses the present two holes in front of Receiver; Requires drill & tap one hole in Rear Top of Rec. Bridge. Inlet Stock: No Access: Tube Dia. 3/4", 7/8" & 1" Rings. Example: Leopold, Lyman, etc. Weaver
"QC"	"QC"	12.50	(For their letter to S.M. Alvis 4-13-48)			