

APPROX. RANGE (YARDS) FOR THE REAR SIGHT STEP
ON REMINGTON RIFLES

10/11/48
CCL

C. F. HI-POWER

<u>Model</u>	<u>Caliber</u>	<u>Notch</u>	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>
81	.25 Rem.	Range	100	170	250	325	395	465	565	630
	.30 Rem.	Range	100	170	245	310	370	440	515	590
	.32 Rem.	Range	100	165	240	310	375	440	515	590
	.35 Rem.	Range	100	165	250	330	415	500	575	660
	.300 Sav	Range	100	165	255	345	420	495	585	675
141	.25 Rem.	Range	100	160	235	315	380	460	545	615
	.30 Rem.	Range	100	160	230	295	355	425	515	580
	.32 Rem.	Range	100	160	230	300	360	430	515	590
	.35 Rem.	Range	100	160	240	315	390	490	570	640
721	.270 Win	Range	100	190	270	335	380	470	490	
	.30-06	Range	100	185	260	325	365	430	465	
	.300 Mag.	Range	100	175	255	320	355	415	450	
722	.257 Rob	Range	100	160	215	275	315	375	410	
	.300 Sav	Range	100	165	215	270	315	375	405	

RIM FIRE

141, 241	.22 L.R.	Range	25	35	45	60	70	80	100
510, 511	.22 L.R.	Range	25	35	45	60	70	80	100
512, 514	.22 L.R.	Range	25	35	45	60	70	80	100
513 S.A.	.22 L.R.	Range	25	60	90	100	170		
550-1	.22 L.R.	Range	25	35	50	60	80	90	110

NOTE: RANGES ORIENTIATED FROM ACTUAL MEASUREMENTS OF REAR SIGHT STEPS TAKEN FROM CURRENT PRODUCT.

THIS DESIGN AND PRINT ARE THE PROPERTY OF

REMINGTON ARMS COMPANY, INC.

OCT 25 1946

THIS PRINT MUST BE RETURNED WITH QUOTATION OR UPON DELIVERY OF
MATERIAL AND EQUIPMENT AND MUST NOT BE USED IN MANUFACTURING
FOR OTHERS EXCEPT BY PERMISSION OF OWNERS.