

Original 9/13/54

REVISED 6/6/55 4-16-58

REMINGTON STANDARDS - ARMS

SHEET 2

MODEL 40X RANGEMASTER	3-2 Std. Bbl.	H-2 Heavy Bbl.	3-1 (With Sights)	H-1 (With Sights)
BARREL Length Shape Muzzle Finish Material Rifling Bore Diameter Groove Diameter Groove Width NOTE: No con-	28" tolerance $\pm 1/16"$ measured from face of locked bolt. Round, tapered No crown, counter sink Black, medium lustre; bluing, minimum 2 coats. High strength, steel alloy 6 grooves, 1 turn in 16" RH 21.77" min.; 21.82" max. 22.17" min.; 22.22" max. .087" min.; .089" max. 22 Long rifle only - Special design for match shooting. Target type (see SCOPE MOUNTS) (Redfield type) See SIGHTS (Front plug screws (2) provided)	heavy	light	heavy
Chamber Scope Mounts Sights Weight Bedding	adjustable (see STOCK)	heavy	light	heavy
BOLT Locking Lugs Extractor Finish	Locking lugs (2) Front section of Bolt Plug. Type horizontally opposed. Bolt head - Right Remainder of bolt assembly - Black Bolt Handle - Slight overbore			
BOLT STOP RELEASE	Located in head of trigger (on trigger housing assembly)			
BUTY PLATE	Non slip hard rubber base, white line, thin soft rubber pad, grooved			
GUN LENGTH	46-3/4" overall			